

COIL-OVER | 1.63" I.D.



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
5.00 (length in inches)														
0500.163.0080	5.00	127	1.63	41	80	14	1.46	37	3.54	90	283	1,259	0.36	0.16
0500.163.0085	5.00	127	1.63	41	85	15	1.40	36	3.60	91	306	1,361	0.35	0.16
0500.163.0090	5.00	127	1.63	41	90	16	1.45	37	3.55	90	320	1,423	0.37	0.17
0500.163.0095	5.00	127	1.63	41	95	17	1.47	37	3.53	90	335	1,490	0.38	0.17
0500.163.0100	5.00	127	1.63	41	100	18	1.52	39	3.48	88	348	1,548	0.40	0.18
0500.163.0105	5.00	127	1.63	41	105	18	1.57	40	3.43	87	360	1,601	0.43	0.20
0500.163.0110	5.00	127	1.63	41	110	19	1.53	39	3.47	88	382	1,699	0.41	0.19
0500.163.0115	5.00	127	1.63	41	115	20	1.55	39	3.45	88	396	1,761	0.43	0.20
0500.163.0120	5.00	127	1.63	41	120	21	1.63	41	3.37	86	405	1,802	0.46	0.21
0500.163.0125	5.00	127	1.63	41	125	22	1.68	43	3.32	84	415	1,846	0.48	0.22
0500.163.0130	5.00	127	1.63	41	130	23	1.73	44	3.27	83	425	1,890	0.50	0.23
0500.163.0135	5.00	127	1.63	41	135	24	1.78	45	3.22	82	434	1,931	0.53	0.24
0500.163.0140	5.00	127	1.63	41	140	25	1.73	44	3.27	83	457	2,033	0.52	0.24
0500.163.0145	5.00	127	1.63	41	145	25	1.68	43	3.32	84	481	2,140	0.50	0.23
0500.163.0150	5.00	127	1.63	41	150	26	1.74	44	3.26	83	490	2,180	0.53	0.24

COIL-OVER | 1.88" I.D.

8.00 (length in inches)															
	0800.188.0100	8.00	203	1.88	48	100	18	2.60	66	5.40	137	539	2,398	1.06	0.48
NEW	0800.188.0180	8.00	203	1.88	48	180	32	3.15	80	4.85	123	873	3,883	1.51	0.68
	0800.188.0185	8.00	203	1.88	48	185	32	3.31	84	4.69	119	868	3,861	1.61	0.73
	0800.188.0200	8.00	203	1.88	48	200	35	3.16	80	4.84	123	967	4,301	1.61	0.73
	0800.188.0225	8.00	203	1.88	48	225	39	3.27	83	4.73	120	1,063	4,728	1.73	0.78
	0800.188.0250	8.00	203	1.88	48	250	44	3.28	83	4.72	120	1,181	5,253	1.78	0.81
	0800.188.0280	8.00	203	1.88	48	280	49	3.42	87	4.58	116	1,281	5,698	1.86	0.84
NEW	0800.188.0300	8.00	203	1.88	48	300	53	3.50	89	4.50	114	1,350	5,989	2.03	0.92
	0800.188.0325	8.00	203	1.88	48	325	57	3.63	92	4.37	111	1,421	6,321	2.16	0.98
	0800.188.0350	8.00	203	1.88	48	350	61	3.76	96	4.24	108	1,484	6,601	2.31	1.05
10.00 (length in inches)															
	1000.188.0050	10.00	254	1.88	48	50	9	2.49	63	7.51	191	376	1,673	0.86	0.39
NEW	1000.188.0060	10.00	254	1.88	48	60	11	2.60	66	7.40	188	444	1,975	0.95	0.43
NEW	1000.188.0070	10.00	254	1.88	48	70	12	2.76	70	7.24	184	506	2,252	1.06	0.48
NEW	1000.188.0080	10.00	254	1.88	48	80	14	2.95	75	7.05	179	564	2,509	1.19	0.54
NEW	1000.188.0090	10.00	254	1.88	48	90	16	2.99	76	7.01	178	631	2,807	1.26	0.57
NEW	1000.188.0100	10.00	254	1.88	48	100	18	3.27	83	6.73	171	673	2,994	1.41	0.64
NEW	1000.188.0110	10.00	254	1.88	48	110	19	3.27	83	6.73	171	740	3,292	1.41	0.64
NEW	1000.188.0120	10.00	254	1.88	48	120	21	3.46	88	6.54	166	784	3,487	1.54	0.70
	1000.188.0130	10.00	254	1.88	48	130	23	3.57	91	6.43	163	835	3,714	1.71	0.78
	1000.188.0145	10.00	254	1.88	48	145	25	4.25	108	5.75	146	834	3,710	2.14	0.97
	1000.188.0160	10.00	254	1.88	48	160	28	3.83	97	6.17	157	987	4,390	1.96	0.89
	1000.188.0175	10.00	254	1.88	48	175	31	3.98	101	6.02	153	1,053	4,684	2.10	0.95
NEW	1000.188.0185	10.00	254	1.88	48	185	32	4.36	111	5.64	143	1,043	4,641	2.20	1.00
	1000.188.0200	10.00	254	1.88	48	200	35	3.99	101	6.01	153	1,203	5,351	2.18	0.99
	1000.188.0225	10.00	254	1.88	48	225	39	4.56	116	5.44	138	1,223	5,440	2.60	1.18
	1000.188.0250	10.00	254	1.88	48	250	44	4.55	116	5.45	138	1,363	6,063	2.73	1.24
	1000.188.0275	10.00	254	1.88	48	275	48	4.63	118	5.37	136	1,478	6,574	2.86	1.30
	1000.188.0300	10.00	254	1.88	48	300	53	4.39	112	5.61	142	1,683	7,486	2.65	1.20
	1000.188.0325	10.00	254	1.88	48	325	57	4.50	114	5.50	140	1,787	7,949	2.79	1.27

COIL-OVER | 1.88" I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
1000.188.0350	10.00	254	1.88	48	350	61	4.67	119	5.33	135	1,865	8,296	2.98	1.35
1000.188.0400	10.00	254	1.88	48	400	70	4.57	116	5.43	138	2,171	9,657	2.99	1.36
1000.188.0450	10.00	254	1.88	48	450	79	4.94	125	5.06	129	2,277	10,129	3.42	1.55
Helper (prevents main spring from becoming loose at full droop)														
HELPER188	2.98	76	1.88	48	12	2								
Coupling Spacer (ID locating main to helper/tender)														
NEW SPACER188			1.88	48										
Torsion Release Bearing														
TRB188			1.88	48										

COIL-OVER | 2.00" I.D.

4.00 (length in inches)														
0400.200.0350	4.00	102	2.00	51	350	61	1.61	41	2.39	61	837	3,723	0.81	0.37
0400.200.0550	4.00	102	2.00	51	550	96	1.73	44	2.27	58	1,248	5,551	0.99	0.45
0400.200.0650	4.00	102	2.00	51	650	114	2.03	52	1.97	50	1,282	5,703	1.28	0.58
0400.200.0700	4.00	102	2.00	51	700	123	1.95	50	2.05	52	1,436	6,388	1.22	0.55
0400.200.0750	4.00	102	2.00	51	750	131	2.00	51	2.00	51	1,501	6,677	1.29	0.59
0400.200.0800	4.00	102	2.00	51	800	140	2.02	51	1.98	50	1,586	7,055	1.23	0.56
0400.200.0850	4.00	102	2.00	51	850	149	1.93	49	2.07	53	1,760	7,890	1.19	0.54
NEW 0400.200.0900	4.00	102	2.00	51	900	158	2.01	51	1.99	51	1,791	8,039	1.28	0.58
NEW 0400.200.0950	4.00	102	2.00	51	950	166	2.13	54	1.89	48	1,774	7,961	1.37	0.62
NEW 0400.200.1000	4.00	102	2.00	51	1,000	175	2.05	52	1.95	50	1,950	8,757	1.30	0.59
0400.200.1050	4.00	102	2.00	51	1,050	184	2.13	54	1.87	48	1,964	8,827	1.41	0.64
NEW 0400.200.1100	4.00	102	2.00	51	1,100	193	2.05	52	1.95	50	2,145	9,632	1.37	0.62
0400.200.1150	4.00	102	2.00	51	1,150	201	2.17	55	1.83	46	2,104	9,359	1.48	0.67
0400.200.1250	4.00	102	2.00	51	1,250	219	2.17	55	1.83	46	2,283	10,155	1.51	0.68
0400.200.1400	4.00	102	2.00	51	1,400	245	2.20	56	1.80	46	2,524	11,227	1.56	0.71
0400.200.1700	4.00	102	2.00	51	1,700	298	2.36	60	1.64	42	2,784	12,384	1.82	0.83
0400.200.1800	4.00	102	2.00	51	1,800	315	2.26	57	1.74	44	3,125	13,901	1.74	0.79
0400.200.1900	4.00	102	2.00	51	1,900	333	2.33	59	1.67	42	3,165	14,079	1.83	0.83
0400.200.2100	4.00	102	2.00	51	2,100	368	2.36	60	1.64	42	3,444	15,447	1.90	0.86
0400.200.2200	4.00	102	2.00	51	2,200	385	2.40	61	1.60	41	3,521	15,662	1.96	0.89
0400.200.2400	4.00	102	2.00	51	2,400	420	2.42	61	1.58	40	3,797	16,890	2.39	1.08
0400.200.2600	4.00	102	2.00	51	2,600	455	2.44	62	1.56	40	4,067	18,091	2.43	1.10
0400.200.2800	4.00	102	2.00	51	2,800	490	2.58	66	1.42	36	3,974	17,677	2.31	1.05
0400.200.3000	4.00	102	2.00	51	3,000	525	2.50	64	1.50	38	4,511	20,066	2.20	1.00
0400.200.3500	4.00	102	2.00	51	3,500	613	2.66	68	1.34	34	4,699	20,902	2.53	1.15
5.00 (length in inches)														
0500.200.0250	5.00	127	2.00	51	250	44	1.97	50	3.03	77	758	3,372	0.93	0.42
0500.200.0400	5.00	127	2.00	51	400	70	2.29	58	2.71	69	1,082	4,813	1.28	0.58
0500.200.0425	5.00	127	2.00	51	425	74	2.30	58	2.70	69	1,147	5,102	1.38	0.63
NEW 0500.200.0450	5.00	127	2.00	51	450	79	2.24	57	2.76	70	1,242	5,517	1.32	0.60
NEW 0500.200.0500	5.00	127	2.00	51	500	88	2.24	57	2.76	70	1,380	6,130	1.39	0.63
NEW 0500.200.0550	5.00	127	2.00	51	550	96	2.32	59	2.68	68	1,474	6,550	1.45	0.66
NEW 0500.200.0600	5.00	127	2.00	51	600	105	2.36	60	2.64	67	1,584	7,040	1.54	0.70
NEW 0500.200.0650	5.00	127	2.00	51	650	114	2.32	59	2.68	68	1,742	7,741	1.45	0.66
0500.200.0700	5.00	127	2.00	51	700	123	2.38	60	2.62	67	1,836	8,167	1.52	0.69
0500.200.0725	5.00	127	2.00	51	725	127	2.34	59	2.66	68	1,932	8,594	1.49	0.68
0500.200.0750	5.00	127	2.00	51	750	131	2.45	62	2.55	65	1,909	8,492	1.62	0.73

COIL-OVER | 2.00" I.D.



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0500.200.0800	5.00	127	2.00	51	800	140	2.56	65	2.44	62	1,956	8,701	1.73	0.78
0500.200.0950	5.00	127	2.00	51	950	166	2.63	67	2.37	60	2,255	10,031	1.87	0.85
0500.200.1000	5.00	127	2.00	51	1,000	175	2.54	65	2.46	62	2,464	10,960	1.80	0.82
0500.200.1050	5.00	127	2.00	51	1,050	184	2.64	67	2.36	60	2,481	11,036	1.92	0.87
0500.200.1100	5.00	127	2.00	51	1,100	193	2.74	70	2.26	57	2,485	11,054	2.05	0.93
0500.200.1200	5.00	127	2.00	51	1,200	210	2.77	70	2.23	57	2,672	11,886	2.13	0.97
NEW 0500.200.1300	5.00	127	2.00	51	1,300	228	2.81	71	2.19	56	2,853	12,691	2.20	1.00
0500.200.1350	5.00	127	2.00	51	1,350	236	2.73	69	2.27	58	3,063	13,625	2.14	0.97
0500.200.1400	5.00	127	2.00	51	1,400	245	2.86	73	2.14	54	2,994	13,318	2.30	1.04
0500.200.1500	5.00	127	2.00	51	1,500	263	2.92	74	2.08	53	3,122	13,887	2.40	1.09
0500.200.1600	5.00	127	2.00	51	1,600	280	2.79	71	2.21	56	3,536	15,729	2.28	1.03
0500.200.1700	5.00	127	2.00	51	1,700	298	2.84	72	2.16	55	3,667	16,312	2.38	1.08
0500.200.1750	5.00	127	2.00	51	1,750	306	2.98	76	2.02	51	3,541	15,751	2.56	1.16
0500.200.1900	5.00	127	2.00	51	1,900	333	2.98	76	2.02	51	3,843	17,094	2.61	1.18
NEW 0500.200.2400	5.00	127	2.00	51	2,400	420	3.19	81	1.81	46	4,334	19,278	3.05	1.38
Torsion Release Bearing														
TRB200			2.00	51										

COIL-OVER | 2.25" I.D.

4.00 (length in inches)														
Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0400.225.0450	4.00	102	2.25	57	450	79	1.61	41	2.39	61	1,076	4,087	1.01	0.46
0400.225.0500	4.00	102	2.25	57	500	88	1.66	42	2.34	59	1,168	5,195	1.08	0.49
0400.225.0550	4.00	102	2.25	57	550	96	1.71	43	2.29	58	1,260	5,605	1.14	0.52
0400.225.0700	4.00	102	2.25	57	700	123	1.82	46	2.18	55	1,529	6,801	1.21	0.55
0400.225.0800	4.00	102	2.25	57	800	140	1.82	46	2.18	55	1,745	7,762	1.24	0.56
0400.225.0825	4.00	102	2.25	57	825	144	1.85	47	2.15	55	1,772	7,882	1.28	0.58
0400.225.0850	4.00	102	2.25	57	850	149	1.88	48	2.12	54	1,799	8,002	1.32	0.60
0400.225.1000	4.00	102	2.25	57	1,000	175	1.97	50	2.03	52	2,029	9,025	1.46	0.66
NEW 0400.225.1050	4.00	102	2.25	57	1,050	184	1.99	51	2.01	51	2,109	9,381	1.50	0.68
NEW 0400.225.1075	4.00	102	2.25	57	1,075	188	1.99	51	2.01	51	2,158	9,600	1.50	0.68
NEW 0400.225.1100	4.00	102	2.25	57	1,100	193	1.99	51	2.01	51	2,208	9,823	1.50	0.68
0400.225.1200	4.00	102	2.25	57	1,200	210	2.01	51	1.99	51	2,385	10,609	1.56	0.71
0400.225.1250	4.00	102	2.25	57	1,250	219	2.10	53	1.90	48	2,372	10,551	1.68	0.76
0400.225.1300	4.00	102	2.25	57	1,300	228	2.03	52	1.97	50	2,559	11,383	1.61	0.73
0400.225.1350	4.00	102	2.25	57	1,350	236	2.12	54	1.88	48	2,535	11,276	1.73	0.78
0400.225.1400	4.00	102	2.25	57	1,400	245	2.10	53	1.90	48	2,662	11,841	1.71	0.78
0400.225.1800	4.00	102	2.25	57	1,800	315	2.27	58	1.73	44	3,115	13,856	2.03	0.92
0400.225.1900	4.00	102	2.25	57	1,900	333	2.22	56	1.78	45	3,387	15,066	1.97	0.89
0400.225.2000	4.00	102	2.25	57	2,000	350	2.26	57	1.74	44	3,482	15,489	2.06	0.93
0400.225.2300	4.00	102	2.25	57	2,300	403	2.34	59	1.66	42	3,812	16,957	2.23	1.01
0400.225.2400	4.00	102	2.25	57	2,400	420	2.41	61	1.59	40	3,810	16,948	2.35	1.07
0400.225.2500	4.00	102	2.25	57	2,500	438	2.36	60	1.64	42	4,109	18,278	2.28	1.03
NEW 0400.225.2600	4.00	102	2.25	57	2,600	455	2.43	62	1.57	40	4,092	18,202	2.40	1.09
0400.225.2800	4.00	102	2.25	57	2,800	490	2.44	62	1.56	40	4,370	19,439	2.46	1.12
0400.225.3000	4.00	102	2.25	57	3,000	525	2.45	62	1.55	39	4,647	20,671	2.52	1.14
0400.225.3200	4.00	102	2.25	57	3,200	560	2.49	63	1.51	38	4,826	21,467	2.61	1.18
0400.225.3400	4.00	102	2.25	57	3,400	595	2.53	64	1.47	37	4,990	22,197	2.71	1.23

COIL-OVER | 2.25" I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
5.00 (length in inches)														
0500.225.0350	5.00	127	2.25	57	350	61	1.95	50	3.05	77	1,068	4,751	1.24	0.56
0500.225.0400	5.00	127	2.25	57	400	70	1.97	50	3.03	77	1,212	5,394	1.28	0.58
0500.225.0425	5.00	127	2.25	57	425	74	2.15	55	2.85	72	1,212	5,391	1.67	0.76
0500.225.0450	5.00	127	2.25	57	450	79	2.15	55	2.85	72	1,284	5,711	1.49	0.68
0500.225.0500	5.00	127	2.25	57	500	88	2.09	53	2.91	74	1,456	6,477	1.39	0.63
0500.225.0525	5.00	127	2.25	57	525	92	2.18	55	2.82	72	1,481	6,588	1.48	0.67
0500.225.0550	5.00	127	2.25	57	550	96	2.12	54	2.88	73	1,585	7,050	1.43	0.65
0500.225.0600	5.00	127	2.25	57	600	105	2.17	55	2.83	72	1,699	7,557	1.52	0.69
0500.225.0625	5.00	127	2.25	57	625	109	2.29	58	2.71	69	1,697	7,549	1.64	0.74
0500.225.0650	5.00	127	2.25	57	650	114	2.22	56	2.78	71	1,806	8,033	1.59	0.72
0500.225.0675	5.00	127	2.25	57	675	118	2.34	59	2.66	68	1,796	7,989	1.73	0.78
0500.225.0700	5.00	127	2.25	57	700	123	2.30	58	2.70	69	1,894	8,425	1.70	0.77
0500.225.0750	5.00	127	2.25	57	750	131	2.35	60	2.65	67	1,989	8,847	1.78	0.81
0500.225.0800	5.00	127	2.25	57	800	140	2.44	62	2.56	65	2,044	9,092	1.90	0.86
0500.225.0850	5.00	127	2.25	57	850	149	2.33	59	2.67	68	2,269	10,093	1.81	0.82
0500.225.0875	5.00	127	2.25	57	875	153	2.45	62	2.55	65	2,230	9,919	1.95	0.88
0500.225.0900	5.00	127	2.25	57	900	158	2.43	62	2.57	65	2,316	10,302	1.93	0.88
0500.225.0925	5.00	127	2.25	57	925	162	2.38	60	2.62	67	2,421	10,769	1.89	0.86
0500.225.0950	5.00	127	2.25	57	950	166	2.50	64	2.50	64	2,371	10,547	2.04	0.93
0500.225.1000	5.00	127	2.25	57	1,000	175	2.43	62	2.57	65	2,567	11,419	1.98	0.90
0500.225.1050	5.00	127	2.25	57	1,050	184	2.51	64	2.49	63	2,616	11,636	2.09	0.95
0500.225.1100	5.00	127	2.25	57	1,100	193	2.61	66	2.39	61	2,631	11,703	2.23	1.01
0500.225.1125	5.00	127	2.25	57	1,125	197	2.56	65	2.44	62	2,746	12,215	2.18	0.99
0500.225.1150	5.00	127	2.25	57	1,150	201	2.53	64	2.47	63	2,835	12,611	2.16	0.98
0500.225.1200	5.00	127	2.25	57	1,200	210	2.64	67	2.36	60	2,837	12,620	2.31	1.05
0500.225.1250	5.00	127	2.25	57	1,250	219	2.56	65	2.44	62	3,050	13,567	2.23	1.01
0500.225.1300	5.00	127	2.25	57	1,300	228	2.64	67	2.36	60	3,073	13,669	2.35	1.07
0500.225.1350	5.00	127	2.25	57	1,350	236	2.74	70	2.26	57	3,052	13,576	2.51	1.14
0500.225.1400	5.00	127	2.25	57	1,400	245	2.69	68	2.31	59	3,238	14,403	2.45	1.11
0500.225.1450	5.00	127	2.25	57	1,450	254	2.79	71	2.21	56	3,204	14,252	2.61	1.18
0500.225.1500	5.00	127	2.25	57	1,500	263	2.74	70	2.26	57	3,394	15,097	2.56	1.16
0500.225.1525	5.00	127	2.25	57	1,525	267	2.71	69	2.29	58	3,491	15,529	2.53	1.15
0500.225.1550	5.00	127	2.25	57	1,550	271	2.84	72	2.16	55	3,344	14,875	2.72	1.23
0500.225.1600	5.00	127	2.25	57	1,600	280	2.79	71	2.21	56	3,539	15,742	2.66	1.21
0500.225.1700	5.00	127	2.25	57	1,700	298	2.84	72	2.16	55	3,674	16,343	2.77	1.26
0500.225.1750	5.00	127	2.25	57	1,750	306	2.95	75	2.05	52	3,595	15,991	2.94	1.33
0500.225.1800	5.00	127	2.25	57	1,800	315	2.89	73	2.11	54	3,799	16,899	2.89	1.31
0500.225.1850	5.00	127	2.25	57	1,850	324	2.83	72	2.17	55	4,008	17,828	2.82	1.28
0500.225.2100	5.00	127	2.25	57	2,100	368	2.92	74	2.08	53	4,361	19,399	3.26	1.48
0500.225.2400	5.00	127	2.25	57	2,400	420	3.00	76	2.00	51	4,797	21,338	3.23	1.47
0500.225.3100	5.00	127	2.25	57	3,100	543	3.25	83	1.75	44	5,430	24,154	3.85	1.75
0500.225.3400	5.00	127	2.25	57	3,400	595	3.20	81	1.80	46	6,124	27,241	3.86	1.75
0500.225.3500	5.00	127	2.25	57	3,500	613	3.28	83	1.72	44	6,021	26,783	4.02	1.82
0500.225.3600	5.00	127	2.25	57	3,600	630	3.21	82	1.79	45	6,434	28,620	3.93	1.78
0500.225.4100	5.00	127	2.25	57	4,100	718	3.24	82	1.76	45	7,222	32,125	4.10	1.86
6.00 (length in inches)														
0600.225.0125	6.00	152	2.25	57	125	22	2.01	51	3.99	101	499	2,220	0.98	0.44
0600.225.0150	6.00	152	2.25	57	150	26	2.03	52	3.97	101	596	2,651	1.03	0.47
0600.225.0175	6.00	152	2.25	57	175	31	2.16	55	3.84	98	671	2,985	1.17	0.53
0600.225.0200	6.00	152	2.25	57	200	35	2.05	52	3.95	100	790	3,503	1.12	0.51

COIL-OVER | 2.25" I.D.



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0600.225.0225	6.00	152	2.25	57	225	39	2.27	58	3.73	95	838	3,728	1.32	0.60
0600.225.0250	6.00	152	2.25	57	250	44	2.25	57	3.75	95	937	4,168	1.40	0.64
0600.225.0275	6.00	152	2.25	57	275	48	2.40	61	3.60	91	989	4,399	1.48	0.67
0600.225.0300	6.00	152	2.25	57	300	53	2.22	56	3.78	96	1,135	5,049	1.60	0.73
0600.225.0325	6.00	152	2.25	57	325	57	2.57	65	3.43	87	1,114	4,955	1.70	0.77
0600.225.0350	6.00	152	2.25	57	350	61	2.36	60	3.64	92	1,273	5,663	1.61	0.73
0600.225.0375	6.00	152	2.25	57	375	66	2.56	65	3.44	87	1,290	5,738	1.72	0.78
NEW 0600.225.0400	6.00	152	2.25	57	400	70	2.44	62	3.56	90	1,424	6,334	1.64	0.74
NEW 0600.225.0450	6.00	152	2.25	57	450	79	2.44	62	3.56	90	1,601	7,122	1.68	0.76
0600.225.0475	6.00	152	2.25	57	475	83	2.56	65	3.44	87	1,633	7,264	1.82	0.83
0600.225.0500	6.00	152	2.25	57	500	88	2.46	62	3.54	90	1,770	7,873	1.74	0.79
0600.225.0525	6.00	152	2.25	57	525	92	2.60	66	3.40	86	1,784	7,936	1.90	0.86
0600.225.0550	6.00	152	2.25	57	550	96	2.73	69	3.27	83	1,799	8,002	2.05	0.93
0600.225.0575	6.00	152	2.25	57	575	101	2.62	67	3.38	86	1,944	8,647	1.96	0.89
0600.225.0600	6.00	152	2.25	57	600	105	2.75	70	3.25	83	1,952	8,683	2.11	0.96
0600.225.0625	6.00	152	2.25	57	625	109	2.68	68	3.32	84	2,076	9,234	2.06	0.93
0600.225.0650	6.00	152	2.25	57	650	114	2.81	71	3.19	81	2,075	9,230	2.22	1.01
0600.225.0700	6.00	152	2.25	57	700	123	2.87	73	3.13	80	2,193	9,755	2.32	1.05
0600.225.0750	6.00	152	2.25	57	750	131	2.98	76	3.02	77	2,267	10,084	2.47	1.12
0600.225.0800	6.00	152	2.25	57	800	140	2.83	72	3.17	81	2,532	11,263	2.34	1.06
0600.225.0850	6.00	152	2.25	57	850	149	2.89	73	3.11	79	2,640	11,743	2.45	1.11
0600.225.0900	6.00	152	2.25	57	900	158	2.98	76	3.02	77	2,720	12,099	2.58	1.17
0600.225.0950	6.00	152	2.25	57	950	166	3.09	78	2.91	74	2,767	12,308	2.76	1.25
0600.225.1000	6.00	152	2.25	57	1,000	175	2.96	75	3.04	77	3,038	13,514	2.62	1.19
0600.225.1100	6.00	152	2.25	57	1,100	193	3.18	81	2.82	72	3,099	13,785	2.95	1.34
0600.225.1200	6.00	152	2.25	57	1,200	210	3.19	81	2.81	71	3,373	15,004	3.04	1.38
0600.225.1300	6.00	152	2.25	57	1,300	228	3.19	81	2.81	71	3,648	16,227	3.11	1.41
0600.225.1400	6.00	152	2.25	57	1,400	245	3.28	83	2.72	69	3,805	16,925	3.48	1.58
0600.225.1450	6.00	152	2.25	57	1,450	254	3.34	85	2.66	68	3,859	17,166	3.37	1.53
0600.225.1500	6.00	152	2.25	57	1,500	263	3.34	85	2.66	68	3,990	17,748	3.61	1.64
0600.225.1600	6.00	152	2.25	57	1,600	280	3.34	85	2.66	68	4,257	18,936	3.68	1.67
0600.225.1800	6.00	152	2.25	57	1,800	315	3.45	88	2.55	65	4,585	20,395	3.96	1.80
NEW 0600.225.2000	6.00	152	2.25	57	2,000	350	3.54	90	2.46	62	4,920	21,716	3.95	1.79
0600.225.2200	6.00	152	2.25	57	2,200	385	3.69	94	2.31	59	5,092	22,650	4.28	1.94
7.00 (length in inches)														
NEW 0700.225.0200	7.00	178	2.25	57	200	35	2.44	62	4.57	116	914	4,066	1.48	0.67
NEW 0700.225.0225	7.00	178	2.25	57	225	39	2.56	65	4.44	113	999	4,444	1.54	0.70
0700.225.0250	7.00	178	2.25	57	250	44	2.49	63	4.51	115	1,126	5,009	1.61	0.73
NEW 0700.225.0275	7.00	178	2.25	57	275	48	2.64	67	4.36	111	1,199	5,335	1.70	0.77
0700.225.0300	7.00	178	2.25	57	300	53	2.68	68	4.32	110	1,296	5,779	1.83	0.83
0700.225.0325	7.00	178	2.25	57	325	57	2.95	75	4.05	103	1,315	5,849	2.02	0.92
0700.225.0350	7.00	178	2.25	57	350	61	2.68	68	4.32	110	1,513	6,730	1.81	0.82
0700.225.0375	7.00	178	2.25	57	375	66	2.78	71	4.22	107	1,581	7,033	1.94	0.88
0700.225.0400	7.00	178	2.25	57	400	70	2.89	73	4.11	104	1,642	7,304	2.08	0.94
0700.225.0425	7.00	178	2.25	57	425	74	3.05	77	3.95	100	1,680	7,473	2.26	1.03
0700.225.0450	7.00	178	2.25	57	450	79	2.90	74	4.10	104	1,845	8,207	2.14	0.97
0700.225.0475	7.00	178	2.25	57	475	83	3.03	77	3.97	101	1,885	8,385	2.30	1.04
0700.225.0500	7.00	178	2.25	57	500	88	3.14	80	3.86	98	1,927	8,572	2.45	1.11
0700.225.0525	7.00	178	2.25	57	525	92	3.03	77	3.97	101	2,083	9,266	2.36	1.07
0700.225.0550	7.00	178	2.25	57	550	96	3.17	81	3.83	97	2,106	9,368	2.53	1.15
0700.225.0600	7.00	178	2.25	57	600	105	3.24	82	3.76	96	2,257	10,040	2.65	1.20

COIL-OVER | 2.25" I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0700.225.0650	7.00	178	2.25	57	650	114	3.31	84	3.69	94	2,400	10,676	2.78	1.26
0700.225.0700	7.00	178	2.25	57	700	123	3.38	86	3.62	92	2,536	11,281	2.90	1.32
NEW 0700.225.0750	7.00	178	2.25	57	750	131	3.43	87	3.57	91	2,678	11,953	3.02	1.37
0700.225.0800	7.00	178	2.25	57	800	140	3.49	89	3.51	89	2,809	12,495	3.15	1.43
0700.225.0850	7.00	178	2.25	57	850	149	3.56	90	3.44	87	2,926	13,015	3.28	1.49
0700.225.0900	7.00	178	2.25	57	900	158	3.43	87	3.57	91	3,213	14,292	3.15	1.43
0700.225.1000	7.00	178	2.25	57	1,000	175	3.64	92	3.36	85	3,359	14,942	3.50	1.59
0700.225.1100	7.00	178	2.25	57	1,100	193	3.63	92	3.37	86	3,710	16,503	3.57	1.62
8.00 (length in inches)														
NEW 0800.225.0150	8.00	203	2.25	57	150	26	2.72	69	2.72	134	792	3,520	1.61	0.73
0800.225.0200	8.00	203	2.25	57	200	35	2.95	75	5.05	128	1,010	4,493	1.95	0.88
0800.225.0225	8.00	203	2.25	57	225	39	3.10	79	4.90	124	1,102	4,902	2.02	0.92
0800.225.0250	8.00	203	2.25	57	250	44	3.09	78	4.91	125	1,227	5,458	2.13	0.97
0800.225.0275	8.00	203	2.25	57	275	48	3.25	83	4.75	121	1,307	5,814	2.24	1.02
0800.225.0300	8.00	203	2.25	57	300	53	3.03	77	4.97	126	1,490	6,628	2.07	0.94
0800.225.0325	8.00	203	2.25	57	325	57	3.13	80	4.87	124	1,584	7,046	2.20	1.00
0800.225.0350	8.00	203	2.25	57	350	61	3.22	82	4.78	121	1,671	7,433	2.34	1.06
0800.225.0375	8.00	203	2.25	57	375	66	3.30	84	4.70	119	1,762	7,838	2.47	1.12
0800.225.0400	8.00	203	2.25	57	400	70	3.46	88	4.54	115	1,814	8,069	2.66	1.21
0800.225.0425	8.00	203	2.25	57	425	74	3.59	91	4.41	112	1,875	8,340	2.82	1.28
0800.225.0450	8.00	203	2.25	57	450	79	3.43	87	4.57	116	2,055	9,141	2.69	1.22
0800.225.0475	8.00	203	2.25	57	475	83	3.58	91	4.42	112	2,101	9,346	2.89	1.31
0800.225.0500	8.00	203	2.25	57	500	88	3.44	87	4.56	116	2,279	10,137	2.78	1.26
0800.225.0525	8.00	203	2.25	57	525	92	3.59	91	4.41	112	2,318	10,311	2.95	1.34
0800.225.0550	8.00	203	2.25	57	550	96	3.73	95	4.27	108	2,347	10,440	3.16	1.43
0800.225.0600	8.00	203	2.25	57	600	105	3.76	96	4.24	108	2,543	11,312	3.26	1.48
0800.225.0650	8.00	203	2.25	57	650	114	3.81	97	4.19	106	2,721	12,104	3.39	1.54
0800.225.0700	8.00	203	2.25	57	700	123	3.92	100	4.08	104	2,859	12,717	3.57	1.62
0800.225.0750	8.00	203	2.25	57	750	131	3.94	100	4.06	103	3,044	13,540	3.66	1.66
0800.225.0800	8.00	203	2.25	57	800	140	4.04	103	3.96	101	3,165	14,079	3.86	1.75
0800.225.0850	8.00	203	2.25	57	850	149	4.12	105	3.88	99	3,299	14,675	4.01	1.82
0800.225.0900	8.00	203	2.25	57	900	158	4.20	107	3.80	97	3,424	15,231	4.17	1.89
0800.225.1000	8.00	203	2.25	57	1,000	175	4.13	105	3.87	98	3,866	17,197	4.19	1.90
9.00 (length in inches)														
0900.225.0175	9.00	229	2.25	57	175	31	3.10	79	5.90	150	1,032	4,591	1.90	0.86
0900.225.0200	9.00	229	2.25	57	200	35	3.43	87	5.57	142	1,114	4,974	2.25	1.02
0900.225.0250	9.00	229	2.25	57	250	44	3.50	89	5.50	140	1,375	6,116	2.43	1.10
0900.225.0300	9.00	229	2.25	57	300	53	3.64	92	5.36	136	1,608	7,153	2.66	1.21
0900.225.0350	9.00	229	2.25	57	350	61	3.85	98	5.15	131	1,801	8,011	2.98	1.35
0900.225.0400	9.00	229	2.25	57	400	70	3.76	96	5.24	133	2,094	9,315	2.98	1.35
0900.225.0450	9.00	229	2.25	57	450	79	4.02	102	4.98	126	2,239	9,960	3.35	1.52
0900.225.0500	9.00	229	2.25	57	500	88	4.02	102	4.98	126	2,492	11,085	3.42	1.55
0900.225.0550	9.00	229	2.25	57	550	96	4.05	103	4.95	126	2,721	12,104	3.53	1.60
0900.225.0600	9.00	229	2.25	57	600	105	4.39	112	4.61	117	2,764	12,295	4.03	1.83
0900.225.0700	9.00	229	2.25	57	700	123	4.49	114	4.51	115	3,159	14,052	4.30	1.95
0900.225.0800	9.00	229	2.25	57	800	140	4.60	117	4.40	112	3,519	15,653	4.61	2.09
0900.225.0900	9.00	229	2.25	57	900	158	4.80	122	4.20	107	3,782	16,823	5.00	2.27
Tender/Linear														
0175.225.0150	2.71	69	2.25	57	150	26	0.97	25	1.75	44	263	1,170	0.88	0.40
0175.225.0250	3.35	85	2.25	57	250	44	1.60	41	1.75	44	438	1,948	1.59	0.72
0175.225.0300	4.26	108	2.25	57	300	53	2.51	64	1.75	44	525	2,335	2.07	0.94

COIL-OVER | 2.25" I.D.



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0225.225.0150	3.84	98	2.25	57	150	26	1.59	40	2.25	57	338	1,503	2.34	1.06
0225.225.0200	3.76	96	2.25	57	200	35	1.51	38	2.25	57	450	2,002	1.72	0.78
Helper														
HELPER225	3.05	77	2.25	57	12	2								
Coupling Spacer (ID locating main to helper/tender)														
SPACER225			2.25	57										
Torsion Release Bearing														
TRB225			2.25	57										
			Fitment Length											
			inch		mm									
NEW ESB09.225			8.00-9.00		203-229									

COIL-OVER | 2.50" I.D.

6.00 (length in inches)														
0600.250.0400	6.00	152	2.50	64	400	70	2.40	61	3.60	91	1,439	6,401	1.85	0.84
0600.250.0450	6.00	152	2.50	64	450	79	2.39	61	3.61	92	1,624	7,224	1.90	0.86
0600.250.0500	6.00	152	2.50	64	500	88	2.38	60	3.62	92	1,809	8,047	1.92	0.87
0600.250.0550	6.00	152	2.50	64	550	96	2.44	62	3.56	90	1,960	8,718	2.03	0.92
0600.250.0600	6.00	152	2.50	64	600	105	2.68	68	3.32	84	1,990	8,852	2.35	1.07
0600.250.0650	6.00	152	2.50	64	650	114	2.69	68	3.31	84	2,149	9,559	2.42	1.10
0600.250.0700	6.00	152	2.50	64	700	123	2.57	65	3.43	87	2,397	10,662	2.29	1.04
0600.250.0750	6.00	152	2.50	64	750	131	2.65	67	3.35	85	2,510	11,165	2.42	1.10
0600.250.0800	6.00	152	2.50	64	800	140	2.71	69	3.29	84	2,634	11,717	2.53	1.15
0600.250.0850	6.00	152	2.50	64	850	149	2.79	71	3.21	82	2,732	12,152	2.67	1.21
0600.250.0900	6.00	152	2.50	64	900	158	2.87	73	3.13	80	2,820	12,544	2.82	1.28
0600.250.0950	6.00	152	2.50	64	950	166	2.92	74	3.08	78	2,924	13,007	2.93	1.33
0600.250.0975	6.00	152	2.50	64	975	171	3.03	77	2.97	75	2,896	12,882	3.11	1.41
0600.250.1000	6.00	152	2.50	64	1,000	175	2.92	74	3.08	78	3,076	13,683	3.00	1.36
0600.250.1100	6.00	152	2.50	64	1,100	193	3.00	76	3.00	76	3,295	14,657	3.15	1.43
0600.250.1150	6.00	152	2.50	64	1,150	201	3.11	79	2.89	73	3,318	14,759	3.35	1.52
0600.250.1200	6.00	152	2.50	64	1,200	210	3.03	77	2.97	75	3,562	15,844	3.24	1.47
NEW 0600.250.1300	6.00	152	2.50	64	1,300	228	3.19	81	2.81	71	365	16,165	3.57	1.62
0600.250.1450	6.00	152	2.50	64	1,450	254	3.16	80	2.84	72	4,110	18,282	3.59	1.63
7.00 (length in inches)														
0700.250.0275	7.00	178	2.50	64	275	48	2.54	65	4.46	113	1,226	5,453	1.95	0.88
0700.250.0300	7.00	178	2.50	64	300	53	2.48	63	4.52	115	1,356	6,032	1.83	0.83
0700.250.0325	7.00	178	2.50	64	325	57	2.54	65	4.46	113	1,449	6,445	1.92	0.87
0700.250.0350	7.00	178	2.50	64	350	61	2.65	67	4.35	110	1,525	6,784	2.06	0.93
0700.250.0375	7.00	178	2.50	64	375	66	2.71	69	4.29	109	1,609	7,157	2.17	0.98
0700.250.0400	7.00	178	2.50	64	400	70	2.81	71	4.19	106	1,675	7,451	2.32	1.05
0700.250.0450	7.00	178	2.50	64	450	79	2.81	71	4.19	106	1,884	8,380	2.36	1.07
0700.250.0500	7.00	178	2.50	64	500	88	2.81	71	4.19	106	2,096	9,323	2.42	1.10
0700.250.0550	7.00	178	2.50	64	550	96	3.07	78	3.93	100	2,161	9,613	2.79	1.27
0700.250.0600	7.00	178	2.50	64	600	105	3.09	78	3.91	99	2,348	10,444	2.87	1.30
0700.250.0650	7.00	178	2.50	64	650	114	3.15	80	3.85	98	2,504	11,138	3.00	1.36
NEW 0700.250.0700	7.00	178	2.50	64	700	123	3.20	81	3.80	97	2,660	11,834	2.93	1.33
NEW 0700.250.0800	7.00	178	2.50	64	800	140	3.35	85	3.65	93	2,918	12,978	3.22	1.46
NEW 0700.250.0900	7.00	178	2.50	64	900	158	3.51	89	3.49	89	3,142	13,978	3.53	1.60

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
NEW 0700.250.1000	7.00	178	2.50	64	1,000	175	3.52	89	3.48	88	3,481	15,484	3.62	1.64
NEW 0700.250.1100	7.00	178	2.50	64	1,100	193	3.70	94	3.30	84	3,626	16,131	3.97	1.80
8.00 (length in inches)														
0800.250.0150	8.00	203	2.50	64	150	26	2.55	65	5.45	138	817	3,634	1.63	0.74
0800.250.0200	8.00	203	2.50	64	200	35	2.67	68	5.33	135	1,065	4,737	1.95	0.88
0800.250.0250	8.00	203	2.50	64	250	44	2.83	72	5.17	131	1,291	5,743	2.12	0.96
0800.250.0300	8.00	203	2.50	64	300	53	2.96	75	5.04	128	1,513	6,730	2.33	1.06
0800.250.0350	8.00	203	2.50	64	350	61	3.12	79	4.88	124	1,709	7,602	2.59	1.17
0800.250.0400	8.00	203	2.50	64	400	70	3.08	78	4.92	125	1,968	8,754	2.61	1.18
0800.250.0450	8.00	203	2.50	64	450	79	3.28	83	4.72	120	2,122	9,439	2.94	1.33
0800.250.0500	8.00	203	2.50	64	500	88	3.28	83	4.72	120	2,358	10,489	3.00	1.36
0800.250.0550	8.00	203	2.50	64	550	96	3.57	91	4.43	113	2,437	10,840	3.44	1.56
0800.250.0600	8.00	203	2.50	64	600	105	3.59	91	4.41	112	2,646	11,770	3.53	1.60
0800.250.0650	8.00	203	2.50	64	650	114	3.63	92	4.37	111	2,838	12,624	3.66	1.66
0800.250.0700	8.00	203	2.50	64	700	123	3.65	93	4.35	110	3,043	13,536	3.75	1.70
0800.250.0750	8.00	203	2.50	64	750	131	3.72	94	4.28	109	3,209	14,274	3.90	1.77
0800.250.0800	8.00	203	2.50	64	800	140	3.79	96	4.21	107	3,368	14,982	4.06	1.84
0800.250.0850	8.00	203	2.50	64	850	149	3.86	98	4.14	105	3,520	15,658	4.23	1.92
0800.250.0900	8.00	203	2.50	64	900	158	3.93	100	4.07	103	3,665	16,303	4.39	1.99
0800.250.0950	8.00	203	2.50	64	950	166	4.02	102	3.98	101	3,776	16,796	4.61	2.09
0800.250.1000	8.00	203	2.50	64	1,000	175	4.12	105	3.88	99	3,877	17,246	4.80	2.18
0800.250.1100	8.00	203	2.50	64	1,100	193	4.07	103	3.93	100	4,317	19,203	4.85	2.20
0800.250.1200	8.00	203	2.50	64	1,200	210	4.30	109	3.70	94	4,437	19,737	5.33	2.42
0800.250.0175	8.00	203	2.50	64	175	31	2.68	68	5.32	135	931	4,141	1.90	0.86
0800.250.0225	8.00	203	2.50	64	225	39	2.71	69	5.29	134	1,191	5,298	2.03	0.92
0800.250.0275	8.00	203	2.50	64	275	48	2.89	73	5.11	130	1,406	6,254	2.21	1.00
0800.250.0325	8.00	203	2.50	64	325	57	3.05	77	4.95	126	1,609	7,157	2.46	1.12
0800.250.0375	8.00	203	2.50	64	375	66	3.23	82	4.77	121	1,787	7,949	2.76	1.25
0800.250.0425	8.00	203	2.50	64	425	74	3.17	81	4.83	123	2,053	9,132	2.76	1.25
0800.250.0475	8.00	203	2.50	64	475	83	3.40	86	4.60	117	2,184	9,715	3.12	1.42
0800.250.0525	8.00	203	2.50	64	525	92	3.42	87	4.58	116	2,402	10,685	3.22	1.46
0800.250.0825	8.00	203	2.50	64	825	144	3.94	100	4.06	103	3,348	14,893	4.32	1.96
0800.250.1025	8.00	203	2.50	64	1,025	179	4.06	103	3.94	100	4,033	17,940	4.74	2.15
8.00 (length in inches) (Silver)														
0800.250.0150S	8.00	203	2.50	64	150	26	2.55	65	5.45	138	817	3,634	1.63	0.74
0800.250.0200S	8.00	203	2.50	64	200	35	2.67	68	5.33	135	1,065	4,737	1.94	0.88
0800.250.0250S	8.00	203	2.50	64	250	44	2.83	72	5.17	131	1,291	5,743	2.12	0.96
0800.250.0300S	8.00	203	2.50	64	300	53	2.96	75	5.04	128	1,513	6,730	2.34	1.06
0800.250.0350S	8.00	203	2.50	64	350	61	3.12	79	4.88	124	1,709	7,602	2.58	1.17
0800.250.0400S	8.00	203	2.50	64	400	70	3.08	78	4.92	125	1,968	8,754	2.62	1.19
0800.250.0500S	8.00	203	2.50	64	500	88	3.28	83	4.72	120	2,358	10,489	3.00	1.36
0800.250.0550S	8.00	203	2.50	64	550	96	3.57	91	4.43	113	2,437	10,840	3.44	1.56
0800.250.0600S	8.00	203	2.50	64	600	105	3.59	91	4.41	112	2,646	11,770	3.53	1.60
10.00 (length in inches)														
1000.250.0100	10.00	254	2.50	64	100	18	3.28	83	6.72	171	671	2,985	2.11	0.96
1000.250.0150	10.00	254	2.50	64	150	26	3.52	89	6.48	165	972	4,324	2.51	1.14
1000.250.0162	10.00	254	2.50	64	162	28	3.61	92	6.39	162	1,035	4,604	2.67	1.21
1000.250.0175	10.00	254	2.50	64	175	31	3.32	84	6.68	170	1,169	5,200	2.51	1.14
1000.250.0200	10.00	254	2.50	64	200	35	3.39	86	6.61	168	1,323	5,885	2.53	1.15
1000.250.0225	10.00	254	2.50	64	225	39	3.39	86	6.61	168	1,487	6,614	2.62	1.19

COIL-OVER | 2.50" I.D.



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
1000.250.0250	10.00	254	2.50	64	250	44	3.72	94	6.28	160	1,569	6,979	3.06	1.39
1000.250.0275	10.00	254	2.50	64	275	48	3.77	96	6.23	158	1,715	7,629	3.17	1.44
1000.250.0300	10.00	254	2.50	64	300	53	3.85	98	6.15	156	1,844	8,202	3.33	1.51
1000.250.0325	10.00	254	2.50	64	325	57	3.94	100	6.06	154	1,971	8,767	3.49	1.58
1000.250.0350	10.00	254	2.50	64	350	61	4.02	102	5.98	152	2,092	9,306	3.66	1.66
1000.250.0375	10.00	254	2.50	64	375	66	4.11	104	5.89	150	2,208	9,822	3.83	1.74
1000.250.0400	10.00	254	2.50	64	400	70	4.24	108	5.76	146	2,302	10,240	4.05	1.84
1000.250.0425	10.00	254	2.50	64	425	74	4.36	111	5.64	143	2,399	10,671	4.25	1.93
1000.250.0450	10.00	254	2.50	64	450	79	4.16	106	5.84	148	2,630	11,699	4.03	1.83
1000.250.0500	10.00	254	2.50	64	500	88	4.43	113	5.57	141	2,786	12,393	4.52	2.05
1000.250.0525	10.00	254	2.50	64	525	92	4.59	117	5.41	137	2,840	12,633	4.80	2.18
1000.250.0550	10.00	254	2.50	64	550	96	4.43	113	5.57	141	3,061	13,616	4.63	2.10
1000.250.0575	10.00	254	2.50	64	575	101	4.57	116	5.43	138	3,121	13,883	4.87	2.21
1000.250.0600	10.00	254	2.50	64	600	105	4.74	120	5.26	134	3,158	14,047	5.18	2.35
1000.250.0650	10.00	254	2.50	64	650	114	4.77	121	5.23	133	3,401	15,128	5.31	2.41
1000.250.0700	10.00	254	2.50	64	700	123	4.80	122	5.20	132	3,644	16,209	5.44	2.47
1000.250.0750	10.00	254	2.50	64	750	131	4.85	123	5.15	131	3,860	17,170	5.62	2.55
1000.250.0800	10.00	254	2.50	64	800	140	4.91	125	5.09	129	4,074	18,122	5.80	2.63
10.00 (length in inches) (Silver)														
1000.250.0100S	10.00	254	2.50	64	100	18	3.28	83	6.72	171	671	2,985	2.12	0.96
1000.250.0150S	10.00	254	2.50	64	150	26	3.52	89	6.48	165	972	4,324	2.51	1.14
1000.250.0175S	10.00	254	2.50	64	175	31	3.32	84	6.68	170	1,169	5,200	2.51	1.14
1000.250.0200S	10.00	254	2.50	64	200	35	3.39	86	6.61	168	1,323	5,885	2.53	1.15
1000.250.0225S	10.00	254	2.50	64	225	39	3.39	86	6.61	168	1,487	6,614	2.62	1.19
1000.250.0250S	10.00	254	2.50	64	250	44	3.72	94	6.28	160	1,569	6,979	3.06	1.39
1000.250.0275S	10.00	254	2.50	64	275	48	3.77	96	6.23	158	1,715	7,629	3.17	1.44
1000.250.0300S	10.00	254	2.50	64	300	53	3.85	98	6.15	156	1,844	8,202	3.33	1.51
1000.250.0325S	10.00	254	2.50	64	325	57	3.94	100	6.06	154	1,971	8,767	3.48	1.58
1000.250.0350S	10.00	254	2.50	64	350	61	4.02	102	5.98	152	2,092	9,306	3.66	1.66
1000.250.0375S	10.00	254	2.50	64	375	66	4.11	104	5.89	150	2,208	9,822	3.83	1.74
1000.250.0400S	10.00	254	2.50	64	400	70	4.24	108	5.76	146	2,302	10,240	4.06	1.84
1000.250.0425S	10.00	254	2.50	64	425	74	4.36	111	5.64	143	2,399	10,671	4.25	1.93
1000.250.0450S	10.00	254	2.50	64	450	79	4.16	106	5.84	148	2,630	11,699	4.03	1.83
1000.250.0500S	10.00	254	2.50	64	500	88	4.43	113	5.57	141	2,786	12,393	4.52	2.05
1000.250.0550S	10.00	254	2.50	64	550	96	4.43	113	5.57	141	3,061	13,616	4.63	2.10
1000.250.0600S	10.00	254	2.50	64	600	105	4.74	120	5.26	134	3,158	14,047	5.18	2.35
1000.250.0650S	10.00	254	2.50	64	650	114	4.77	121	5.23	133	3,401	15,128	5.31	2.41
1000.250.0700S	10.00	254	2.50	64	700	123	4.80	122	5.20	132	3,644	16,209	5.44	2.47
1000.250.0750S	10.00	254	2.50	64	750	131	4.85	123	5.15	131	3,860	17,170	5.62	2.55
1000.250.0800S	10.00	254	2.50	64	800	140	4.91	125	5.09	129	4,074	18,122	5.80	2.63
10.00 (length in inches) XT Barrel (Extreme Travel)														
NEW 1000.2530.0300	10.00	254	2.5/3.0	64/76	300	53	3.15	80	6.85	174	2,050	9,119	3.46	1.57
NEW 1000.2530.0325	10.00	254	2.5/3.0	64/76	325	57	3.27	83	6.73	171	2,184	9,715	3.66	1.66
NEW 1000.2530.0350	10.00	254	2.5/3.0	64/76	350	61	3.39	86	6.61	168	2,311	10,280	3.86	1.75
NEW 1000.2530.0375	10.00	254	2.5/3.0	64/76	375	66	3.50	89	6.50	165	2,432	10,818	4.08	1.85
NEW 1000.2530.0400	10.00	254	2.5/3.0	64/76	400	70	3.62	92	6.38	162	2,546	11,325	4.30	1.95
NEW 1000.2530.0425	10.00	254	2.5/3.0	64/76	425	74	3.74	95	6.26	159	2,660	11,832	4.52	2.05
NEW 1000.2530.0450	10.00	254	2.5/3.0	64/76	450	79	3.94	100	6.06	154	2,728	12,135	4.80	2.18
NEW 1000.2530.0475	10.00	254	2.5/3.0	64/76	475	83	3.94	100	6.06	154	2,879	12,806	4.80	2.18
NEW 1000.2530.0500	10.00	254	2.5/3.0	64/76	500	88	4.02	102	5.98	152	2,992	13,309	4.98	2.26

COIL-OVER | 2.50" I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
12.00 (length in inches)														
1200.250.0090	12.00	305	2.50	64	90	16	3.82	97	8.18	208	736	3,274	2.51	1.14
1200.250.0100	12.00	305	2.50	64	100	18	3.51	89	8.49	216	849	3,777	2.31	1.05
1200.250.0110	12.00	305	2.50	64	110	19	3.53	90	8.47	215	932	4,146	2.45	1.11
1200.250.0120	12.00	305	2.50	64	120	21	3.66	93	8.34	212	1,001	4,453	2.62	1.19
1200.250.0125	12.00	305	2.50	64	125	22	3.95	100	8.05	204	1,007	4,479	2.92	1.32
1200.250.0130	12.00	305	2.50	64	130	23	4.38	111	7.62	194	991	4,408	3.26	1.48
1200.250.0140	12.00	305	2.50	64	140	25	4.01	102	7.99	203	1,118	4,973	3.05	1.38
1200.250.0150	12.00	305	2.50	64	150	26	4.19	106	7.81	198	1,171	5,209	3.29	1.49
1200.250.0165	12.00	305	2.50	64	165	29	3.94	100	8.06	205	1,330	5,916	3.00	1.36
1200.250.0175	12.00	305	2.50	64	175	31	4.16	106	7.84	199	1,372	6,103	3.26	1.48
1200.250.0185	12.00	305	2.50	64	185	32	3.95	100	8.05	204	1,488	6,619	3.11	1.41
1200.250.0200	12.00	305	2.50	64	200	35	4.07	103	7.93	201	1,585	7,050	3.28	1.49
1200.250.0225	12.00	305	2.50	64	225	39	4.46	113	7.54	192	1,696	7,544	3.80	1.72
1200.250.0250	12.00	305	2.50	64	250	44	4.43	113	7.57	192	1,893	8,420	3.86	1.75
1200.250.0275	12.00	305	2.50	64	275	48	4.48	114	7.52	191	2,067	9,194	4.01	1.82
1200.250.0300	12.00	305	2.50	64	300	53	4.96	126	7.04	179	2,112	9,395	4.67	2.12
1200.250.0325	12.00	305	2.50	64	325	57	5.02	128	6.98	177	2,270	10,097	4.84	2.20
1200.250.0350	12.00	305	2.50	64	350	61	5.12	130	6.88	175	2,408	10,711	5.05	2.29
1200.250.0375	12.00	305	2.50	64	375	66	5.22	133	6.78	172	2,542	11,307	5.27	2.39
1200.250.0400	12.00	305	2.50	64	400	70	5.32	135	6.68	170	2,670	11,877	5.51	2.50
1200.250.0425	12.00	305	2.50	64	425	74	5.43	138	6.57	167	2,794	12,428	5.73	2.60
1200.250.0450	12.00	305	2.50	64	450	79	5.22	133	6.78	172	3,052	13,576	5.51	2.50
1200.250.0475	12.00	305	2.50	64	475	83	5.34	136	6.66	169	3,162	14,065	5.75	2.61
1200.250.0525	12.00	305	2.50	64	525	92	5.65	144	6.35	161	3,334	14,830	6.37	2.89
1200.250.0600	12.00	305	2.50	64	600	105	5.82	148	6.18	157	3,706	16,485	6.83	3.10
1200.250.0625	12.00	305	2.50	64	625	109	5.62	143	6.38	162	3,985	17,726	6.59	2.99
1200.250.0800	12.00	305	2.50	64	800	140	5.92	150	6.08	154	4,864	21,636	7.49	3.40
12.00 (length in inches) (Silver)														
1200.250.0100S	12.00	305	2.50	64	100	18	3.51	89	8.49	216	849	3,777	2.31	1.05
1200.250.0125S	12.00	305	2.50	64	125	22	3.95	100	8.05	204	1,007	4,479	2.91	1.32
1200.250.0150S	12.00	305	2.50	64	150	26	4.19	106	7.81	198	1,171	5,209	3.28	1.49
1200.250.0175S	12.00	305	2.50	64	175	31	4.16	106	7.84	199	1,372	6,103	3.26	1.48
1200.250.0200S	12.00	305	2.50	64	200	35	4.07	103	7.93	201	1,585	7,050	3.28	1.49
1200.250.0225S	12.00	305	2.50	64	225	39	4.46	113	7.54	192	1,696	7,544	3.79	1.72
1200.250.0250S	12.00	305	2.50	64	250	44	4.43	113	7.57	192	1,893	8,420	3.86	1.75
1200.250.0275S	12.00	305	2.50	64	275	48	4.48	114	7.52	191	2,067	9,194	4.01	1.82
1200.250.0300S	12.00	305	2.50	64	300	53	4.96	126	7.04	179	2,112	9,395	4.67	2.12
1200.250.0325S	12.00	305	2.50	64	325	57	5.02	128	6.98	177	2,270	10,097	4.83	2.19
1200.250.0350S	12.00	305	2.50	64	350	61	5.12	130	6.88	175	2,408	10,711	5.05	2.29
1200.250.0375S	12.00	305	2.50	64	375	66	5.22	133	6.78	172	2,542	11,307	5.27	2.39
1200.250.0400S	12.00	305	2.50	64	400	70	5.32	135	6.68	170	2,670	11,877	5.51	2.50
1200.250.0425S	12.00	305	2.50	64	425	74	5.43	138	6.57	167	2,794	12,428	5.73	2.60
1200.250.0450S	12.00	305	2.50	64	450	79	5.22	133	6.78	172	3,052	13,576	5.51	2.50
1200.250.0475S	12.00	305	2.50	64	475	83	5.34	136	6.66	169	3,162	14,065	5.75	2.61
1200.250.0500S	12.00	305	2.50	64	500	88	5.49	139	6.51	165	3,252	14,466	6.06	2.75
1200.250.0525S	12.00	305	2.50	64	525	92	5.65	144	6.35	161	3,334	14,830	6.37	2.89
1200.250.0550S	12.00	305	2.50	64	550	96	5.83	148	6.17	157	3,390	15,079	6.72	3.05
1200.250.0600S	12.00	305	2.50	64	600	105	5.82	148	6.18	157	3,706	16,485	6.83	3.10
1200.250.0650S	12.00	305	2.50	64	650	114	5.81	148	6.19	157	4,025	17,904	6.94	3.15
1200.250.0700S	12.00	305	2.50	64	700	123	5.85	149	6.15	156	4,307	19,158	7.12	3.23

COIL-OVER | 2.50" I.D.



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
1200.250.0750S	12.00	305	2.50	64	750	131	5.88	149	6.12	155	4,586	20,399	7.32	3.32
1200.250.0800S	12.00	305	2.50	64	800	140	5.92	150	6.08	154	4,864	21,636	7.49	3.40
1200.250.0900S	12.00	305	2.50	64	900	158	6.40	163	5.60	142	5,041	22,423	8.60	3.90
12.00 (length in inches) XT Barrel (Extreme Travel)														
NEW 1200.2530.0100	12.00	305	2.5/3.0	64/76	100	18	2.68	68	9.32	237	932.00	4,146	2.42	1.10
1200.2530.0125	12.00	305	2.5/3.0	64/76	125	22	2.83	72	9.17	233	1,146	5,098	2.67	1.21
1200.2530.0150	12.00	305	2.5/3.0	64/76	150	26	3.04	77	8.96	228	1,344	5,978	3.00	1.36
1200.2530.0175	12.00	305	2.5/3.0	64/76	175	31	3.29	84	8.71	221	1,524	6,779	3.37	1.53
1200.2530.0200	12.00	305	2.5/3.0	64/76	200	35	3.28	83	8.72	221	1,744	7,758	3.42	1.55
1200.2530.0225	12.00	305	2.5/3.0	64/76	225	39	3.61	92	8.39	213	1,888	8,398	3.95	1.79
1200.2530.0250	12.00	305	2.5/3.0	64/76	250	44	3.66	93	8.34	212	2,085	9,274	4.06	1.84
NEW 1200.2530.0275	12.00	305	2.5/3.0	64/76	275	48	3.70	94	8.30	211	2,282	10,151	4.19	1.90
NEW 1200.2530.0300	12.00	305	2.5/3.0	64/76	300	53	4.17	106	7.83	199	2,350	10,453	4.90	2.22
NEW 1200.2530.0325	12.00	305	2.5/3.0	64/76	325	57	4.25	108	7.75	197	2,519	11,205	5.07	2.30
NEW 1200.2530.0350	12.00	305	2.5/3.0	64/76	350	61	4.38	111	7.62	194	2,666	11,859	5.34	2.42
NEW 1200.2530.0375	12.00	305	2.5/3.0	64/76	375	66	4.17	106	7.83	199	2,934	13,051	5.07	2.30
NEW 1200.2530.0400	12.00	305	2.5/3.0	64/76	400	70	4.31	109	7.69	195	3,077	13,687	5.31	2.41
NEW 1200.2530.0425	12.00	305	2.5/3.0	64/76	425	74	4.45	113	7.56	192	3,213	14,292	5.55	2.52
14.00 (length in inches)														
1400.250.0080	14.00	356	2.50	64	80	14	3.93	100	10.07	256	806	3,585	2.56	1.16
1400.250.0090	14.00	356	2.50	64	90	16	4.81	122	9.19	233	827	3,679	3.39	1.54
1400.250.0095	14.00	356	2.50	64	95	17	4.59	117	9.41	239	894	3,977	3.24	1.47
1400.250.0100	14.00	356	2.50	64	100	18	4.39	112	9.61	244	961	4,275	3.09	1.40
1400.250.0110	14.00	356	2.50	64	110	19	5.03	128	8.97	228	987	4,390	3.77	1.71
1400.250.0120	14.00	356	2.50	64	120	21	4.55	116	9.45	240	1,134	5,044	3.48	1.58
1400.250.0130	14.00	356	2.50	64	130	23	4.84	123	9.16	233	1,190	5,293	3.72	1.69
1400.250.0140	14.00	356	2.50	64	140	25	4.53	115	9.47	241	1,326	5,898	3.48	1.58
1400.250.0150	14.00	356	2.50	64	150	26	4.72	120	9.28	236	1,391	6,187	3.72	1.69
1400.250.0165	14.00	356	2.50	64	165	29	4.80	122	9.20	234	1,518	6,752	3.90	1.77
1400.250.0175	14.00	356	2.50	64	175	31	5.04	128	8.96	228	1,568	6,975	4.21	1.91
1400.250.0185	14.00	356	2.50	64	185	32	4.76	121	9.24	235	1,709	7,602	3.99	1.81
1400.250.0200	14.00	356	2.50	64	200	35	4.92	125	9.08	231	1,817	8,082	4.21	1.91
1400.250.0225	14.00	356	2.50	64	225	39	5.32	135	8.68	220	1,953	8,687	4.80	2.18
1400.250.0250	14.00	356	2.50	64	250	44	5.32	135	8.68	220	2,170	9,653	4.91	2.23
1400.250.0275	14.00	356	2.50	64	275	48	5.79	147	8.21	209	2,258	10,044	5.62	2.55
1400.250.0300	14.00	356	2.50	64	300	53	5.81	148	8.19	208	2,458	10,934	5.77	2.62
1400.250.0325	14.00	356	2.50	64	325	57	5.90	150	8.10	206	2,633	11,712	5.99	2.72
1400.250.0350	14.00	356	2.50	64	350	61	5.96	151	8.04	204	2,812	12,508	6.19	2.81
1400.250.0400	14.00	356	2.50	64	400	70	6.19	157	7.81	198	3,123	13,892	6.72	3.05
1400.250.0450	14.00	356	2.50	64	450	79	6.48	165	7.52	191	3,385	15,057	7.34	3.33
1400.250.0500	14.00	356	2.50	64	500	88	6.34	161	7.66	195	3,830	17,037	7.34	3.33
14.00 (length in inches) (Silver)														
1400.250.0100S	14.00	356	2.50	64	100	18	4.39	112	9.61	244	961	4,275	3.09	1.40
1400.250.0125S	14.00	356	2.50	64	125	22	5.00	127	9.00	229	1,125	5,004	3.86	1.75
1400.250.0150S	14.00	356	2.50	64	150	26	4.72	120	9.28	236	1,391	6,187	3.72	1.69
1400.250.0175S	14.00	356	2.50	64	175	31	5.04	128	8.96	228	1,568	6,975	4.21	1.91
1400.250.0185S	14.00	356	2.50	64	185	32	4.78	121	9.22	234	1,705	7,584	3.99	1.81
1400.250.0200S	14.00	356	2.50	64	200	35	4.92	125	9.08	231	1,817	8,082	4.21	1.91
1400.250.0225S	14.00	356	2.50	64	225	39	5.32	135	8.68	220	1,953	8,687	4.80	2.18
1400.250.0250S	14.00	356	2.50	64	250	44	5.32	135	8.68	220	2,170	9,653	4.91	2.23
1400.250.0275S	14.00	356	2.50	64	275	48	5.79	147	8.21	209	2,258	10,044	5.62	2.55

COIL-SLEEVE | 2.50" I.D.



Part Number	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
	inch	mm	inch	mm	inch	mm
Coil Sleeve (Fits 2.50" I.D. Springs)						
NEW CS3001	2.50-3.50	64-89	0.423-0.541	11-14	10.31	262
NEW CS3002	2.50-3.50	64-89	0.551-0.650	14-17	10.31	262

	Fitment Length	
	inch	mm
SPRING BAGS-Pair (Fits 2.50" I.D. Springs)		
NEW ESB10.250	8.00-10.00	203-254
NEW ESB12.250	10.00-12.00	254-305
NEW ESB14.250	12.00-14.00	305-356
NEW ESB16.250	14.00-16.00	356-406
SPRING BAGS-Pair (Fits 2.50" I.D. XT Barrel Springs)		
NEW ESB12.300	10.00-12.00	254-305
NEW ESB14.300	12.00-14.00	305-356
NEW ESB16.300	14.00-16.00	356-406

COIL-OVER | 3.00" I.D. Silver

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
4.00 (length in inches) (Silver)														
NEW 0400.300.0500S	4.00	102	3.00	76	500	88	1.46	37	2.54	65	1,272	5,657	2.20	1.00
8.00 (length in inches) (Silver)														
0800.300.0100S	8.00	203	3.00	76	100	18	2.01	51	5.99	152	599	2,664	1.69	0.77
10.00 (length in inches) (Silver)														
1000.300.0100S	10.00	254	3.00	76	100	18	2.83	72	7.17	182	716	3,185	2.55	1.16
1000.300.0150S	10.00	254	3.00	76	150	26	2.91	74	7.09	180	1,063	4,728	2.54	1.15
1000.300.0200S	10.00	254	3.00	76	200	35	3.07	78	6.93	176	1,382	6,147	2.93	1.33
1000.300.0250S	10.00	254	3.00	76	250	44	3.35	85	6.65	169	1,662	7,393	3.43	1.56
1000.300.0300S	10.00	254	3.00	76	300	53	3.31	84	6.69	170	2,008	8,932	3.57	1.62
12.00 (length in inches) (Silver)														
NEW 1200.300.0100S	12.00	305	3.00	76	100	18	2.87	73	9.13	232	912	4,057	2.34	1.06
NEW 1200.300.0125S	12.00	305	3.00	76	125	22	3.35	85	8.65	220	1,079	4,800	2.98	1.35
NEW 1200.300.0150S	12.00	305	3.00	76	150	26	3.19	81	8.81	224	1,319	5,867	2.89	1.31
NEW 1200.300.0175S	12.00	305	3.00	76	175	31	3.74	95	8.26	210	1,448	6,441	3.66	1.66
NEW 1200.300.0200S	12.00	305	3.00	76	200	35	3.66	93	8.34	212	1,664	7,402	3.70	1.68
NEW 1200.300.0225S	12.00	305	3.00	76	225	39	3.94	100	8.06	205	1,815	8,073	4.17	1.89
NEW 1200.300.0250S	12.00	305	3.00	76	250	44	3.94	100	8.06	205	2,014	8,959	4.28	1.94
NEW 1200.300.0275S	12.00	305	3.00	76	275	48	4.29	109	7.71	196	2,122	9,439	4.87	2.21
NEW 1200.300.0300S	12.00	305	3.00	76	300	53	4.33	110	7.67	195	2,305	10,253	5.03	2.28
NEW 1200.300.0325S	12.00	305	3.00	76	325	57	4.37	111	7.63	194	2,486	11,058	5.16	2.34
1200.300.0350S	12.00	305	3.00	76	350	61	4.41	112	7.59	193	2,657	11,819	5.36	2.43
1200.300.0375S	12.00	305	3.00	76	375	66	4.49	114	7.51	191	2,815	12,522	5.58	2.53
1200.300.0400S	12.00	305	3.00	76	400	70	4.57	116	7.43	189	2,970	13,211	5.80	2.63
1200.300.0450S	12.00	305	3.00	76	450	79	4.76	121	7.24	184	3,254	14,474	6.28	2.85
1200.300.0500S	12.00	305	3.00	76	500	88	5.00	127	7.00	178	3,503	15,582	6.86	3.11
1200.300.0600S	12.00	305	3.00	76	600	105	5.24	133	6.76	172	4,069	18,100	7.61	3.45
14.00 (length in inches) (Silver)														
NEW 1400.300.0125S	14.00	356	3.00	76	125	22	3.98	101	10.02	255	1,254	5,578	3.77	1.71
NEW 1400.300.0150S	14.00	356	3.00	76	150	26	4.25	108	9.75	248	1,464	6,512	4.21	1.91

COIL-SLEEVE | 3.00" I.D.

Part Number	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
	inch	mm	inch	mm	inch	mm
Coil Sleeve (Fits 3.00" I.D. Springs)						
NEW CS3001	2.50-3.50	64-89	0.423-0.541	11-14	10.31	262
NEW CS3002	2.50-3.50	64-89	0.551-0.650	14-17	10.31	262

	Fitment Length	
	inch	mm
SPRING BAGS-Pair (Fits 3.00" I.D. Springs)		
NEW ESB14.300	12.00-14.00	305-356
NEW ESB16.300	14.00-16.00	356-406

COIL-OVER | 3.75" I.D. (Off-Road Silver)

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
10.00 (length in inches) (Silver)														
1000.375.0250S	10.00	254	3.75	95	250	44	2.95	75	7.05	179	1,762	7,838	3.95	1.79
1000.375.0300S	10.00	254	3.75	95	300	53	3.19	81	6.81	173	2,043	9,088	4.56	2.07
1000.375.0350S	10.00	254	3.75	95	350	61	3.27	83	6.73	171	2,356	10,480	4.85	2.20
1000.375.0400S	10.00	254	3.75	95	400	70	3.39	86	6.61	168	2,645	11,765	5.22	2.37
1000.375.0450S	10.00	254	3.75	95	450	79	3.50	89	6.50	165	2,923	13,002	5.62	2.55
1000.375.0500S	10.00	254	3.75	95	500	88	3.66	93	6.34	161	3,169	14,096	6.13	2.78
12.00 (length in inches) (Silver)														
1200.375.0200S	12.00	305	3.75	95	200	35	3.38	86	8.62	219	1,725	7,673	4.39	1.99
1200.375.0250S	12.00	305	3.75	95	250	44	3.56	90	8.44	214	2,111	9,390	4.94	2.24
1200.375.0300S	12.00	305	3.75	95	300	53	3.84	98	8.16	207	2,447	10,885	5.69	2.58
1200.375.0350S	12.00	305	3.75	95	350	61	4.17	106	7.83	199	2,741	12,193	6.57	2.98
1200.375.0400S	12.00	305	3.75	95	400	70	4.28	109	7.72	196	3,087	13,732	7.01	3.18
1200.375.0500S	12.00	305	3.75	95	500	88	4.57	116	7.43	189	3,716	16,530	8.04	3.65
1200.375.0700S	12.00	305	3.75	95	700	123	4.96	126	7.04	179	4,927	21,916	10.05	4.56
14.00 (length in inches) (Silver)														
1400.375.0300S	14.00	356	3.75	95	300	53	4.71	120	9.29	236	2,787	12,397	7.49	3.40
1400.375.0350S	14.00	356	3.75	95	350	61	5.04	128	8.96	228	3,135	13,945	8.51	3.86
1400.375.0400S	14.00	356	3.75	95	400	70	5.15	131	8.85	225	3,541	15,751	9.01	4.09
1400.375.0450S	14.00	356	3.75	95	450	79	5.28	134	8.72	221	3,925	17,459	9.57	4.34
18.00 (length in inches) (Silver)														
1800.375.0700S	18.00	457	3.75	95	700	123	8.72	221	9.28	236	6,499	28,909	21.69	9.84
1800.375.0750S	18.00	457	3.75	95	750	131	9.01	229	8.99	228	6,741	29,985	23.08	10.47
1800.375.0800S	18.00	457	3.75	95	800	140	8.95	227	9.05	230	7,239	32,201	23.23	10.54
20.00 (length in inches) (Silver)														
2000.375.0300S	20.00	508	3.75	95	300	53	7.36	187	12.64	321	3,792	16,868	13.62	6.18
2000.375.0400S	20.00	508	3.75	95	400	70	8.21	209	11.79	299	4,716	20,978	16.84	7.64
2000.375.0500S	20.00	508	3.75	95	500	88	9.06	230	10.94	278	5,471	24,336	20.98	9.52
2000.375.0600S	20.00	508	3.75	95	600	105	9.49	241	10.51	267	6,307	28,055	23.32	10.58
2000.375.0650S	20.00	508	3.75	95	650	114	9.76	248	10.24	260	6,654	29,598	24.68	11.19
2000.375.0675S	20.00	508	3.75	95	675	118	9.88	251	10.12	257	6,831	30,386	25.35	11.50
2000.375.0700S	20.00	508	3.75	95	700	123	10.04	255	9.96	253	6,973	31,017	26.12	11.85
2000.375.0750S	20.00	508	3.63	95	750	131	10.40	264	9.60	244	7,197	32,014	27.84	12.63

COIL-OVER | 3.75" I.D. (Off-Road Silver)

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
22.00 (length in inches) (Silver)														
2200.375.0300S	22.00	559	3.75	95	300	53	8.31	211	13.69	348	4,107	18,269	16.00	7.26
2200.375.0400S	22.00	559	3.75	95	400	70	9.16	233	12.84	326	5,135	22,842	19.48	8.84
2200.375.0500S	22.00	559	3.75	95	500	88	10.07	256	11.93	303	5,964	26,529	24.07	10.92
2200.375.0550S	22.00	559	3.75	95	550	96	10.41	264	11.59	294	6,373	28,348	26.29	11.93
2200.375.0600S	22.00	559	3.63	95	600	105	11.00	279	11.00	279	6,601	29,363	28.28	12.83
2200.375.0700S	22.00	559	3.63	95	700	123	11.09	282	10.91	277	7,638	33,975	29.71	13.48
2200.375.0800S	22.00	559	3.63	95	800	140	11.82	300	10.18	259	8,136	36,191	33.43	15.16
24.00 (length in inches) (Silver)														
2400.375.0300S	24.00	610	3.75	95	300	53	9.37	238	14.63	372	4,388	19,519	18.73	8.50
2400.375.0350S	24.00	610	3.75	95	350	61	9.78	248	14.22	361	4,977	22,139	20.54	9.32
2400.375.0400S	24.00	610	3.75	95	400	70	10.47	266	13.53	344	5,411	24,069	23.96	10.87
2400.375.0450S	24.00	610	3.75	95	450	79	11.57	294	12.43	316	5,591	24,870	28.15	12.77
2400.375.0500S	24.00	610	3.75	95	500	88	11.16	283	12.84	326	6,419	28,553	27.53	12.49
2400.375.0550S	24.00	610	3.75	95	550	96	11.91	303	12.09	307	6,652	29,589	30.66	13.91
2400.375.0600S	24.00	610	3.75	95	600	105	12.10	307	11.90	302	7,137	31,747	32.05	14.54
2400.375.0650S	24.00	610	3.75	95	650	114	12.65	321	11.35	288	7,380	32,828	34.12	15.48
2400.375.0700S	24.00	610	3.75	95	700	123	12.58	320	11.42	290	7,995	35,563	35.15	15.94
33.00 (length in inches) (Silver)														
3300.375.0115S	33.00	838	3.75	95	115	20	13.29	338	19.71	501	2,267	10,084	23.01	10.44
3300.375.0130S	33.00	838	3.75	95	130	23	13.73	349	19.27	489	2,504	11,138	24.68	11.19
Helper														
HELPER375	6.07	154	3.75	95	45	8								
Coupling Spacer (ID locating main to helper/tender)														
SPACER375			3.75	95										



Conventional Front



Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
8.75 (length in inches) - 5.75" O.D.														
0875.575.0300	8.75	222	5.75	146	300	53	2.66	68	6.05	154	1,815	8,073	3.95	1.79
0875.575.0325	8.75	222	5.75	146	325	57	2.76	70	5.95	151	1,933	8,598	4.19	1.90
0875.575.0350	8.75	222	5.75	146	350	61	2.84	72	5.87	149	2,054	9,137	4.32	1.96
0875.575.0375	8.75	222	5.75	146	375	66	2.91	74	5.80	147	2,175	9,675	5.11	2.32
0875.575.0400	8.75	222	5.75	146	400	70	2.58	66	6.13	156	2,452	10,907	2.64	1.20
0875.575.0425	8.75	222	5.75	146	425	74	2.92	74	5.79	147	2,462	10,951	4.61	2.09
0875.575.0450	8.75	222	5.75	146	450	79	2.84	72	5.87	149	2,640	11,743	4.65	2.11
NEW 0875.575.0460	8.75	222	5.75	146	460	81	2.97	75	5.74	146	2,641	11,748	4.78	2.17
0875.575.0475	8.75	222	5.75	146	475	83	3.02	77	5.69	145	2,703	12,023	4.94	2.24
0875.575.0500	8.75	222	5.75	146	500	88	2.65	67	6.06	154	3,031	13,482	4.65	2.11
0875.575.0525	8.75	222	5.75	146	525	92	3.07	78	5.64	143	2,961	13,171	5.09	2.31
0875.575.0550	8.75	222	5.75	146	550	96	2.99	76	5.72	145	3,145	13,990	5.14	2.33
0875.575.0575	8.75	222	5.75	146	575	101	3.17	81	5.54	141	3,184	14,163	5.42	2.46
0875.575.0600	8.75	222	5.75	146	600	105	3.04	77	5.67	144	3,401	15,128	5.29	2.40
0875.575.0625	8.75	222	5.75	146	625	109	3.22	82	5.49	139	3,429	15,253	5.58	2.53
0875.575.0650	8.75	222	5.75	146	650	114	3.21	82	5.50	140	3,574	15,898	5.86	2.66
0875.575.0675	8.75	222	5.75	146	675	118	3.28	83	5.44	138	3,669	16,320	5.75	2.61
0875.575.0700	8.75	222	5.75	146	700	123	3.08	78	5.63	143	3,941	17,530	5.49	2.49
0875.575.0750	8.75	222	5.75	146	750	131	3.43	87	5.28	134	3,961	17,619	6.26	2.84
0875.575.0800	8.75	222	5.75	146	800	140	3.48	88	5.23	133	4,184	18,611	6.70	3.04
0875.575.0825	8.75	222	5.75	146	825	144	3.48	88	5.23	133	4,315	19,194	6.70	3.04
0875.575.0850	8.75	222	5.75	146	850	149	3.58	91	5.13	130	4,359	19,390	7.07	3.21
0875.575.0875	8.75	222	5.75	146	875	153	3.26	83	5.45	138	4,769	21,213	6.81	3.09
0875.575.0900	8.75	222	5.75	146	900	158	3.69	94	5.03	128	4,523	20,119	7.69	3.49
0875.575.0925	8.75	222	5.75	146	925	162	3.74	95	4.97	126	4,601	20,466	7.65	3.47
0875.575.0950	8.75	222	5.75	146	950	166	3.74	95	4.97	126	4,726	21,022	7.65	3.47
0875.575.0975	8.75	222	5.75	146	975	171	3.74	95	4.97	126	4,849	21,569	7.65	3.47
0875.575.1000	8.75	222	5.75	146	1,000	175	3.79	96	4.92	125	4,923	21,898	7.98	3.62
0875.575.1025	8.75	222	5.75	146	1,025	179	3.79	96	4.92	125	5,046	22,446	7.98	3.62
NEW 0875.575.1050	8.75	222	5.75	146	1,050	184	3.74	95	5.01	127	5,260	23,396	8.04	3.65
NEW 0875.575.1100	8.75	222	5.75	146	1,100	193	3.90	99	4.85	123	5,338	23,743	8.64	3.92
0875.575.1150	8.75	222	5.75	146	1,150	201	4.49	114	4.22	107	4,855	21,596	9.92	4.50
0875.575.1200	8.75	222	5.75	146	1,200	210	3.80	97	4.91	125	5,893	26,213	8.35	3.79
0875.575.1225	8.75	222	5.75	146	1,225	214	3.97	101	4.75	121	5,812	25,853	8.84	4.01
NEW 0875.575.1250	8.75	222	5.75	146	1,250	219	3.90	99	4.85	123	6,065	26,977	8.64	3.92
NEW 0875.575.1300	8.75	222	5.75	146	1,300	228	4.06	103	4.69	119	6,103	27,150	9.26	4.20
0875.575.1325	8.75	222	5.75	146	1,325	232	4.07	103	4.64	118	6,153	27,370	9.26	4.20
NEW 0875.575.1350	8.75	222	5.75	146	1,350	236	4.06	103	4.69	119	6,338	28,194	9.26	4.20
0875.575.1400	8.75	222	5.75	146	1,400	245	3.85	98	4.86	123	6,807	30,279	8.55	3.88
NEW 0875.575.1450	8.75	222	5.75	146	1,450	254	4.06	103	4.69	119	6,808	30,282	9.37	4.25
0875.575.1500	8.75	222	5.75	146	1,500	263	4.22	107	4.49	114	6,741	29,985	9.90	4.49
0875.575.1525	8.75	222	5.75	146	1,525	267	4.22	107	4.49	114	6,853	30,484	9.90	4.49
0875.575.1550	8.75	222	5.75	146	1,550	271	3.84	98	4.87	124	7,541	33,544	9.83	4.46
0875.575.1600	8.75	222	5.75	146	1,600	280	4.04	103	4.67	119	7,466	33,210	9.37	4.25
NEW 0875.575.1650	8.75	222	5.75	146	1,650	289	3.62	92	5.13	130	8,461	37,638	9.28	4.21
0875.575.1700	8.75	222	5.75	146	1,700	298	4.29	109	4.42	112	7,518	33,442	10.40	4.72
0875.575.1750	8.75	222	5.75	146	1,750	306	4.14	105	4.57	116	7,995	35,563	9.76	4.43
0875.575.1800	8.75	222	5.75	146	1,800	315	4.24	108	4.47	114	8,048	35,799	10.18	4.62
0875.575.1850	8.75	222	5.75	146	1,850	324	3.64	92	5.07	129	9,381	41,729	9.52	4.32
0875.575.1900	8.75	222	5.75	146	1,900	333	4.24	108	4.47	114	8,496	37,792	10.18	4.62

Conventional Front

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0875.575.2000	8.75	222	5.75	146	2,000	350	4.29	109	4.42	112	8,845	39,344	10.40	4.72
0875.575.2100	8.75	222	5.75	146	2,100	368	4.34	110	4.37	111	9,185	40,857	10.60	4.81
NEW 0875.575.2200	8.75	222	5.75	146	2,200	385	4.37	111	4.38	111	9,636	42,863	10.40	4.72
NEW 0875.575.2300	8.75	222	5.75	146	2,300	403	4.49	114	4.26	108	9,801	43,596	11.20	5.08
NEW 0875.575.2400	8.75	222	5.75	146	2,400	420	4.53	115	4.22	107	10,132	45,071	11.42	5.18
NEW 0875.575.2500	8.75	222	5.75	146	2,500	438	4.65	118	4.10	104	10,259	45,635	11.86	5.38
NEW 0875.575.2600	8.75	222	5.75	146	2,600	455	4.65	118	4.10	104	10,670	47,461	11.86	5.38
NEW 0875.575.2700	8.75	222	5.75	146	2,700	473	4.65	118	4.10	104	11,080	49,286	11.86	5.38
NEW 0875.575.2800	8.75	222	5.75	146	2,800	490	4.72	120	4.03	102	11,270	50,131	12.32	5.59
9.50 (length in inches) - 5.00" O.D.														
NEW 0950.500.0200	9.50	241	5.00	127	200	35	2.54	65	6.96	177	1,391	6,187	3.17	1.44
NEW 0950.500.0250	9.50	241	5.00	127	250	44	2.58	66	6.92	176	1,730	7,695	3.33	1.51
NEW 0950.500.0300	9.50	241	5.00	127	300	53	2.87	73	6.63	168	1,990	8,852	3.92	1.78
NEW 0950.500.0350	9.50	241	5.00	127	350	61	2.92	74	6.58	167	2,302	10,240	4.32	1.96
NEW 0950.500.0375	9.50	241	5.00	127	375	66	3.20	81	6.30	160	2,363	10,512	4.92	2.23
NEW 0950.500.0400	9.50	241	5.00	127	400	70	3.09	78	6.41	163	2,565	11,410	4.72	2.14
NEW 0950.500.0425	9.50	241	5.00	127	400	70	3.20	81	6.30	160	2,678	11,913	4.98	2.26
0950.500.0450	9.50	241	5.00	127	450	79	3.54	90	5.96	151	2,682	11,930	5.42	2.46
NEW 0950.500.0475	9.50	241	5.00	127	475	83	3.37	86	6.13	156	2,912	12,954	5.42	2.46
0950.500.0500	9.50	241	5.00	127	500	88	3.78	96	5.72	145	2,861	12,726	5.99	2.72
NEW 0950.500.0525	9.50	241	5.00	127	525	92	3.37	86	6.13	156	3,220	14,323	5.49	2.49
0950.500.0550	9.50	241	5.00	127	550	96	3.37	86	6.13	156	3,373	15,004	5.25	2.38
NEW 0950.500.0575	9.50	241	5.00	127	575	101	3.60	91	5.90	150	3,392	15,087	6.04	2.74
0950.500.0600	9.50	241	5.00	127	600	105	3.60	91	5.90	150	3,541	15,751	5.80	2.63
NEW 0950.500.0625	9.50	241	5.00	127	625	109	3.66	93	5.84	148	3,651	16,239	6.24	2.83
0950.500.0650	9.50	241	5.00	127	650	114	3.66	93	5.84	148	3,797	16,890	5.97	2.71
0950.500.0700	9.50	241	5.00	127	700	123	3.93	100	5.57	141	3,895	17,326	6.63	3.01
0950.500.0750	9.50	241	5.00	127	750	131	3.99	101	5.51	140	4,128	18,362	6.83	3.10
0950.500.0775	9.50	241	5.00	127	775	136	4.03	102	5.48	139	4,242	18,867	6.93	3.14
0950.500.0800	9.50	241	5.00	127	800	140	4.06	103	5.44	138	4,355	19,372	7.03	3.19
0950.500.0850	9.50	241	5.00	127	850	149	4.35	110	5.15	131	4,377	19,470	7.69	3.49
0950.500.0900	9.50	241	5.00	127	900	158	4.21	107	5.29	134	4,760	21,173	7.49	3.40
0950.500.0950	9.50	241	5.00	127	950	166	4.55	116	4.95	126	4,704	20,924	8.24	3.74
0950.500.1000	9.50	241	5.00	127	1,000	175	4.65	118	4.85	123	4,852	21,583	8.55	3.88
0950.500.1050	9.50	241	5.00	127	1,050	184	4.54	115	4.96	126	5,205	23,153	8.33	3.78
0950.500.1100	9.50	241	5.00	127	1,100	193	4.61	117	4.89	124	5,382	23,940	8.55	3.88
0950.500.1200	9.50	241	5.00	127	1,200	210	5.05	128	4.45	113	5,340	23,753	10.01	4.54
0950.500.1250	9.50	241	5.00	127	1,250	219	4.90	124	4.60	117	5,750	25,577	9.68	4.39
0950.500.1300	9.50	241	5.00	127	1,300	228	5.34	136	4.16	106	5,413	24,078	10.84	4.92
0950.500.1400	9.50	241	5.00	127	1,400	245	5.03	128	4.47	114	6,259	27,841	10.14	4.60
0950.500.1500	9.50	241	5.00	127	1,500	263	5.35	136	4.15	105	6,218	27,659	11.06	5.02
0950.500.1600	9.50	241	5.00	127	1,600	280	5.57	141	3.93	100	6,289	27,975	11.97	5.43
9.50 (length in inches) - 5.50" O.D.														
NEW 0950.550.0300	9.50	241	5.50	140	300	53	2.60	66	6.90	175	2,068	9,201	4.23	1.92
NEW 0950.550.0325	9.50	241	5.50	140	325	57	2.87	73	6.63	169	2,156	9,589	4.85	2.20
0950.550.0350	9.50	241	5.50	140	350	61	3.08	78	6.42	163	2,247	9,995	5.40	2.45
NEW 0950.550.0375	9.50	241	5.50	140	375	66	2.97	75	6.53	166	2,449	10,893	5.18	2.35
0950.550.0400	9.50	241	5.50	140	400	70	3.37	86	6.13	156	2,452	10,907	5.44	2.47
NEW 0950.550.0425	9.50	241	5.50	140	425	74	3.13	80	6.37	162	2,707	12,041	5.62	2.55
0950.550.0450	9.50	241	5.50	140	450	79	3.10	79	6.40	163	2,880	12,811	5.31	2.41
NEW 0950.550.0475	9.50	241	5.50	140	475	83	3.06	78	6.44	164	3,058	13,601	5.56	2.52

Conventional Front

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
0950.550.0500	9.50	241	5.50	140	500	88	3.26	83	6.24	158	3,117	13,865	5.77	2.62
NEW 0950.550.0525	9.50	241	5.50	140	525	92	3.29	83	6.21	158	3,262	14,509	6.17	2.80
0950.550.0550	9.50	241	5.50	140	550	96	3.53	90	5.97	152	3,281	14,595	6.41	2.91
0950.550.0575	9.50	241	5.50	140	575	101	3.59	91	5.91	150	3,397	15,111	6.59	2.99
0950.550.0600	9.50	241	5.50	140	600	105	3.71	94	5.79	147	3,473	15,449	6.92	3.14
0950.550.0625	9.50	241	5.50	140	625	109	3.74	95	5.76	146	3,600	16,011	7.02	3.18
0950.550.0650	9.50	241	5.50	140	650	114	3.77	96	5.73	146	3,726	16,574	7.12	3.23
0950.550.0675	9.50	241	5.50	140	675	118	3.83	97	5.68	144	3,829	17,032	7.33	3.32
0950.550.0700	9.50	241	5.50	140	700	123	3.88	99	5.62	143	3,932	17,490	7.54	3.42
0950.550.0750	9.50	241	5.50	140	750	131	4.07	103	5.43	138	4,068	18,095	8.04	3.65
0950.550.0800	9.50	241	5.50	140	800	140	4.13	105	5.37	136	4,292	19,092	8.27	3.75
0950.550.0850	9.50	241	5.50	140	850	149	4.19	106	5.31	135	4,511	20,066	8.49	3.85
0950.550.0900	9.50	241	5.50	140	900	158	4.37	111	5.13	130	4,616	20,533	9.54	4.33
0950.550.0950	9.50	241	5.50	140	950	166	4.52	115	4.98	126	4,734	21,058	9.52	4.32
0950.550.1000	9.50	241	5.50	140	1,000	175	4.53	115	4.97	126	4,974	22,125	9.90	4.49
0950.550.1050	9.50	241	5.50	140	1,050	184	4.84	123	4.66	118	4,896	21,778	10.87	4.93
0950.550.1100	9.50	241	5.50	140	1,100	193	4.15	105	5.35	136	5,889	26,195	9.94	4.51
0950.550.1150	9.50	241	5.50	140	1,150	201	4.57	116	4.93	125	5,671	25,226	10.20	4.63
0950.550.1200	9.50	241	5.50	140	1,200	210	4.92	125	4.58	116	5,494	24,438	11.28	5.12
0950.550.1250	9.50	241	5.50	140	1,250	219	4.76	121	4.74	120	5,920	26,333	10.89	4.94
0950.550.1300	9.50	241	5.50	140	1,300	228	5.17	131	4.33	110	5,634	25,061	12.12	5.50
0950.550.1350	9.50	241	5.50	140	1,350	236	5.00	127	4.50	114	6,069	26,996	11.70	5.31
0950.550.1400	9.50	241	5.50	140	1,400	245	4.88	124	4.62	117	6,463	28,749	11.39	5.17
0950.550.1450	9.50	241	5.50	140	1,450	254	5.29	134	4.21	107	6,102	27,143	12.67	5.75
0950.550.1500	9.50	241	5.50	140	1,500	263	5.13	130	4.37	111	6,560	29,180	12.23	5.55
10.50 (length in inches) - 5.50" O.D.														
NEW 1050.550.0300	10.50	267	5.50	140	300	53	2.89	74	7.61	193	2,273	10,112	4.70	2.13
NEW 1050.550.0325	10.50	267	5.50	140	325	57	2.95	75	7.55	192	2,446	10,881	4.85	2.20
NEW 1050.550.0350	10.50	267	5.50	140	350	61	3.00	76	7.50	191	2,617	11,640	5.03	2.28
NEW 1050.550.0375	10.50	267	5.50	140	375	66	3.10	79	7.40	188	2,764	12,297	5.36	2.43
NEW 1050.550.0400	10.50	267	5.50	140	400	70	3.15	80	7.35	187	2,928	13,025	5.53	2.51



Conventional Rear

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
Loaded Height Rear (NASCAR Specs – 700lbs. @ 10.00")														
LH1.500.0125	15.79	401	5.00	127	125	22	4.10	104	11.70	297	1,462	6,503	5.84	2.65
LH1.500.0150	14.88	378	5.00	127	150	26	3.62	92	11.25	286	1,687	7,504	5.05	2.29
LH1.500.0175	14.21	361	5.00	127	175	31	3.81	97	10.38	264	1,817	8,082	5.51	2.50
LH1.500.0200	13.70	348	5.00	127	200	35	3.76	96	9.94	252	1,987	8,839	5.53	2.51
LH1.500.0225	13.31	338	5.00	127	225	39	3.73	95	9.58	243	2,155	9,586	5.58	2.53
NEW LH1.500.0250	12.99	330	5.00	127	250	44	3.70	94	9.29	236	2,323	10,333	5.88	2.67
NEW LH1.500.0275	12.76	324	5.00	127	275	48	4.37	111	8.39	213	2,306	10,258	7.01	3.18
LH1.500.0300	12.52	318	5.00	127	300	53	4.40	112	8.13	207	2,440	10,854	7.14	3.24
LH1.500.0325	12.36	314	5.00	127	325	57	3.84	98	8.51	216	2,765	12,299	6.08	2.76
LH1.500.0350	12.20	310	5.00	127	350	61	3.91	99	8.29	211	2,900	12,900	6.28	2.85
LH1.500.0375	12.05	306	5.00	127	375	66	4.01	102	8.06	205	3,021	13,438	6.55	2.97
LH1.500.0400	11.93	303	5.00	127	400	70	4.07	103	7.87	200	3,149	14,007	6.74	3.06
LH1.500.0425	11.85	301	5.00	127	425	74	4.02	102	7.83	199	3,327	14,799	6.59	2.99
LH1.500.0430	12.01	305	5.00	127	430	75	4.17	106	7.83	199	3,369	14,986	7.01	3.18
LH1.500.0450	11.77	299	5.00	127	450	79	4.05	103	7.70	196	3,465	15,413	6.79	3.08
LH1.500.0475	11.65	296	5.00	127	475	83	4.18	106	7.49	190	3,558	15,827	7.12	3.23
LH1.500.0500	11.61	295	5.00	127	500	88	4.21	107	7.39	188	3,693	16,427	7.05	3.20
LH1.500.0525	11.54	293	5.00	127	525	92	4.44	113	7.09	180	3,722	16,556	7.80	3.54
LH1.500.0550	11.46	291	5.00	127	550	96	4.00	102	7.47	190	4,109	18,278	6.88	3.12
LH1.500.0575	11.42	290	5.00	127	575	101	4.16	106	7.26	184	4,173	18,562	7.25	3.29
LH1.500.0600	11.38	289	5.00	127	600	105	4.29	109	7.08	180	4,230	18,816	7.60	3.45
LH1.500.0650	11.26	286	5.00	127	650	114	4.62	117	6.66	169	4,328	19,252	8.42	3.82
LH1.500.0700	11.18	284	5.00	127	700	123	4.96	126	6.24	158	4,367	19,425	7.89	3.58
LH1.500.0750	11.14	283	5.00	127	750	131	4.72	120	6.41	163	4,808	21,387	8.82	4.00
LH1.500.0800	11.18	284	5.00	127	800	140	5.75	146	5.43	138	4,259	18,945	11.39	5.17
LH1.500.0850	11.14	283	5.00	127	850	149	5.17	131	5.97	152	4,970	22,108	10.07	4.57
LH1.500.0900	11.10	282	5.00	127	900	158	5.61	142	5.49	139	4,909	21,836	11.22	5.09
LH1.500.0925	11.10	282	5.00	127	925	162	5.46	139	5.64	143	5,216	23,202	10.89	4.94
LH1.500.0950	11.10	282	5.00	127	950	166	5.32	135	5.79	147	5,448	24,234	10.58	4.80
LH1.500.0975	11.10	282	5.00	127	975	171	5.24	133	5.86	149	5,528	24,590	10.40	4.72
LH1.500.1000	11.10	282	5.00	127	1,000	175	5.54	141	5.57	141	5,527	24,585	11.77	5.34
LH1.500.1100	11.10	282	5.00	127	1,100	193	5.75	146	5.35	136	5,878	26,146	13.51	6.13
LH1.500.1200	11.10	282	5.00	127	1,200	210	5.71	145	5.39	137	6,464	28,752	13.47	6.11
NEW LH1.500.1300	11.10	282	5.00	127	1,300	228	5.98	152	5.12	130	6,659	29,620	13.40	6.08
LH1.500.1400	11.10	282	5.00	127	1,400	245	5.97	152	5.13	130	7,181	31,943	13.51	6.13
11.00 (length in inches) - 5.00" O.D.														
1100.500.0125	11.00	279	5.00	127	125	22	2.41	61	8.59	218	1,073	4,773	2.93	1.33
1100.500.0150	11.00	279	5.00	127	150	26	2.55	65	8.45	215	1,268	5,640	3.22	1.46
1100.500.0175	11.00	279	5.00	127	175	31	2.73	69	8.27	210	1,447	6,437	3.59	1.63
1100.500.0200	11.00	279	5.00	127	200	35	2.89	73	8.11	206	1,621	7,211	3.97	1.80
1100.500.0225	11.00	279	5.00	127	225	39	3.16	80	7.84	199	1,763	7,842	4.52	2.05
1100.500.0250	11.00	279	5.00	127	250	44	3.17	81	7.83	199	1,957	8,705	4.61	2.09
1100.500.0275	11.00	279	5.00	127	275	48	3.18	81	7.82	199	2,150	9,564	4.67	2.12
1100.500.0300	11.00	279	5.00	127	300	53	3.80	97	7.20	183	2,159	9,604	5.93	2.69
1100.500.0325	11.00	279	5.00	127	325	57	3.33	85	7.67	195	2,493	11,089	5.07	2.30
1100.500.0350	11.00	279	5.00	127	350	61	3.65	93	7.35	187	2,574	11,450	5.75	2.61
1100.500.0375	11.00	279	5.00	127	375	66	4.01	102	6.99	178	2,622	11,663	6.55	2.97
1100.500.0400	11.00	279	5.00	127	400	70	3.83	97	7.17	182	2,867	12,753	6.22	2.82
1100.500.0425	11.00	279	5.00	127	425	74	3.90	99	7.10	180	3,018	13,425	6.44	2.92
1100.500.0450	11.00	279	5.00	127	450	79	3.78	96	7.22	183	3,249	14,452	6.22	2.82

Conventional Rear



Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
1100.500.0500	11.00	279	5.00	127	500	88	4.03	102	6.97	177	3,486	15,506	6.83	3.10
1100.500.0550	11.00	279	5.00	127	550	96	4.29	109	6.71	170	3,690	16,414	7.49	3.40
1100.500.0600	11.00	279	5.00	127	600	105	4.55	116	6.45	164	3,871	17,219	8.20	3.72
1100.500.0650	11.00	279	5.00	127	650	114	4.69	119	6.31	160	4,104	18,255	9.06	4.11
1100.500.0700	11.00	279	5.00	127	700	123	4.69	119	6.31	160	4,420	19,661	8.66	3.93
NEW 1100.500.0750	11.00	279	5.00	127	750	131	4.69	119	6.31	160	4,736	21,067	8.75	3.97
NEW 1100.500.0800	11.00	279	5.00	127	800	140	4.76	121	6.24	158	4,988	22,188	8.99	4.08
NEW 1100.500.0850	11.00	279	5.00	127	850	149	4.80	122	6.20	157	5,267	23,429	9.23	4.19
NEW 1100.500.0900	11.00	279	5.00	127	900	158	4.96	126	6.04	153	5,435	24,176	9.10	4.13
13.00 (length in inches) - 5.00" O.D.														
1300.500.0125	13.00	330	5.00	127	125	22	2.90	74	10.10	257	1,262	5,614	3.70	1.68
1300.500.0150	13.00	330	5.00	127	150	26	3.05	77	9.95	253	1,492	6,637	4.06	1.84
1300.500.0175	13.00	330	5.00	127	175	31	3.49	89	9.51	242	1,663	7,397	4.96	2.25
1300.500.0180	13.00	330	5.00	127	180	32	3.23	82	9.77	248	1,758	7,820	4.47	2.03
1300.500.0200	13.00	330	5.00	127	200	35	3.46	88	9.54	242	1,907	8,483	4.98	2.26
1300.500.0225	13.00	330	5.00	127	225	39	3.70	94	9.30	236	2,092	9,306	5.53	2.51
1300.500.0250	13.00	330	5.00	127	250	44	4.01	102	8.99	228	2,248	10,000	6.19	2.81
1300.500.0275	13.00	330	5.00	127	275	48	4.38	111	8.62	219	2,371	10,547	7.01	3.18
1300.500.0300	13.00	330	5.00	127	300	53	4.10	104	8.90	226	2,671	11,881	6.52	2.96
1300.500.0325	13.00	330	5.00	127	325	57	4.17	106	8.83	224	2,869	12,762	6.74	3.06
1300.500.0350	13.00	330	5.00	127	350	61	4.24	108	8.76	223	3,066	13,638	6.96	3.16
1300.500.0375	13.00	330	5.00	127	375	66	4.31	109	8.69	221	3,258	14,492	7.19	3.26
1300.500.0400	13.00	330	5.00	127	400	70	4.41	112	8.59	218	3,434	15,275	7.47	3.39
1300.500.0450	13.00	330	5.00	127	450	79	4.65	118	8.35	212	3,757	16,712	8.09	3.67
1300.500.0500	13.00	330	5.00	127	500	88	4.93	125	8.07	205	4,036	17,953	8.84	4.01
1300.500.0550	13.00	330	5.00	127	550	96	5.28	134	7.72	196	4,248	18,896	9.72	4.41
1300.500.0600	13.00	330	5.00	127	600	105	5.57	141	7.43	189	4,458	19,830	10.56	4.79
1300.500.0700	13.00	330	5.00	127	700	123	5.59	142	7.41	188	5,186	23,068	10.82	4.91
15.00 (length in inches) - 5.00" O.D.														
1500.500.0125	15.00	381	5.00	127	125	22	4.10	104	10.90	277	1,363	6,063	5.82	2.64
1500.500.0150	15.00	381	5.00	127	150	26	3.86	98	11.14	283	1,670	7,428	5.58	2.53
1500.500.0165	15.00	381	5.00	127	165	29	5.05	128	9.95	253	1,642	7,304	7.89	3.58
1500.500.0175	15.00	381	5.00	127	175	31	4.09	104	10.91	277	1,908	8,487	6.13	2.78
1500.500.0200	15.00	381	5.00	127	200	35	4.36	111	10.64	270	2,128	9,466	6.74	3.06
1500.500.0225	15.00	381	5.00	127	225	39	4.63	118	10.37	263	2,333	10,378	7.41	3.36
1500.500.0250	15.00	381	5.00	127	250	44	4.63	118	10.37	263	2,593	11,534	7.52	3.41
1500.500.0275	15.00	381	5.00	127	275	48	4.65	118	10.35	263	2,846	12,660	7.67	3.48
1500.500.0300	15.00	381	5.00	127	300	53	5.02	128	9.98	253	2,994	13,318	8.53	3.87
16.00 (length in inches) - 5.00" O.D.														
1600.500.0100	16.00	406	5.00	127	100	18	3.34	85	12.66	322	1,265	5,627	4.36	1.98
1600.500.0125	16.00	406	5.00	127	125	22	3.80	97	12.20	310	1,525	6,784	5.25	2.38
1600.500.0150	16.00	406	5.00	127	150	26	3.94	100	12.06	306	1,810	8,051	5.62	2.55
1600.500.0175	16.00	406	5.00	127	175	31	4.17	106	11.83	300	2,070	9,208	6.19	2.81
1600.500.0200	16.00	406	5.00	127	200	35	4.79	122	11.21	285	2,241	9,968	7.52	3.41
1600.500.0225	16.00	406	5.00	127	225	39	4.74	120	11.26	286	2,533	11,267	7.54	3.42
1600.500.0250	16.00	406	5.00	127	250	44	5.11	130	10.89	277	2,723	12,112	8.40	3.81
Rear Platinum Springs - 5.00" O.D.														
NEW ER16.0075	16.00	406	5.00	127	75	13	2.47	63	13.53	344	1,015	4,515	3.10	1.41
NEW ER16.0085	16.00	406	5.00	127	85	15	2.57	65	13.43	341	1,142	5,080	3.25	1.47
NEW ER16.0100	16.00	406	5.00	127	100	18	2.92	74	13.08	332	1,308	5,818	3.90	1.77
NEW ER16.0125	16.00	406	5.00	127	125	22	3.07	78	12.93	328	1,616	7,188	4.60	2.09

Conventional Rear

Platinum Continued

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
NEW ER16.0150	16.00	406	5.00	127	150	26	3.55	90	12.45	316	1,868	8,309	5.10	2.31
NEW ER16.0175	16.00	406	5.00	127	175	31	3.68	93	12.32	313	2,156	9,590	5.60	2.54
NEW ER16.0200	16.00	406	5.00	127	200	35	3.84	98	12.16	309	2,432	10,818	6.10	2.77
NEW ER15.0150	15.00	381	5.00	127	150	26	3.26	83	11.74	298	1,761	7,834	4.72	2.14
NEW ER15.0175	15.00	381	5.00	127	175	31	3.44	87	11.56	294	2,023	8,998	5.18	2.35
NEW ER15.0200	15.00	381	5.00	127	200	35	3.66	93	11.34	288	2,268	10,090	5.71	2.59
NEW ER15.0225	15.00	381	5.00	127	225	39	4.08	104	10.92	277	2,457	10,929	6.55	2.97
NEW ER15.0250	15.00	381	5.00	127	250	44	4.29	109	10.71	272	2,678	11,912	6.90	3.13
NEW ER14.0275	14.00	356	5.00	127	275	48	4.01	102	9.99	254	2,747	12,219	6.20	2.81
NEW ER14.0325	14.00	356	5.00	127	325	57	4.29	109	9.71	247	3,156	14,039	7.20	3.27
NEW ER14.0375	14.00	356	5.00	127	375	66	4.46	113	9.54	242	3,578	15,916	7.67	3.48
NEW ER14.0400	14.00	356	5.00	127	400	70	4.74	120	9.26	235	3,704	16,476	8.45	3.83
NEW ER135.0350	13.50	343	5.00	127	350	61	4.01	102	9.49	241	3,322	14,777	7.47	3.39
NEW ER13.0300	13.00	330	5.00	127	300	53	3.70	94	9.30	236	2,790	12,410	6.44	2.92
NEW ER13.0325	13.00	330	5.00	127	325	57	3.75	95	9.25	235	3,006	13,371	6.59	2.99
NEW ER13.0475	13.00	330	5.00	127	475	83	4.86	123	8.14	207	3,867	17,201	8.55	3.88
NEW ER13.0500	13.00	330	5.00	127	500	88	4.71	120	8.29	211	4,145	18,438	8.55	3.88
NEW ER125.0175	12.50	318	5.00	127	175	31	3.23	82	9.27	235	1,622	7,214	4.48	2.03
NEW ER125.0200	12.50	318	5.00	127	200	35	3.22	82	9.28	236	1,855	8,253	5.00	2.27
NEW ER125.0225	12.50	318	5.00	127	225	39	3.21	82	9.29	236	2,090	9,299	5.05	2.29
NEW ER125.0250	12.50	318	5.00	127	250	44	3.46	88	9.04	230	2,259	10,048	5.64	2.56
NEW ER125.0275	12.50	318	5.00	127	275	48	3.50	89	9.00	229	2,475	11,009	5.77	2.62
NEW ER125.0300	12.50	318	5.00	127	300	53	3.56	90	8.94	227	2,681	11,927	5.95	2.70
NEW ER125.0400	12.50	318	5.00	127	400	70	4.41	112	8.09	205	3,234	14,387	7.47	3.39
NEW ER1225.0325	12.25	311	5.00	127	325	57	3.86	98	8.38	213	2,724	12,119	6.70	3.04
NEW ER1225.0350	12.25	311	5.00	127	350	61	3.93	100	8.32	211	2,911	12,950	6.92	3.14
NEW ER1225.0375	12.25	311	5.00	127	375	66	4.00	102	8.24	209	3,090	13,743	7.16	3.25
NEW ER12.0425	12.00	305	5.00	127	425	74	3.82	97	8.18	208	3,477	15,466	6.99	3.17
NEW ER12.0450	12.00	305	5.00	127	450	79	3.90	99	8.10	206	3,645	16,214	7.26	3.29
NEW ER12.0475	12.00	305	5.00	127	475	83	4.05	103	7.95	202	3,776	16,796	7.61	3.45
NEW ER12.0500	12.00	305	5.00	127	500	88	3.94	100	8.06	205	4,030	17,926	7.48	3.39
NEW ER12.0525	12.00	305	5.00	127	525	92	4.16	106	7.84	199	4,116	18,309	7.75	3.52
NEW ER12.0550	12.00	305	5.00	127	550	96	4.05	103	7.95	202	4,373	19,452	7.70	3.49
NEW ER12.0600	12.00	305	5.00	127	600	105	4.10	104	7.90	201	4,740	21,084	8.00	3.63
NEW ER12.0650	12.00	305	5.00	127	650	114	4.62	117	7.38	187	4,797	21,338	8.80	3.99
NEW ER115.0700	11.50	292	5.00	127	700	123	4.43	113	7.07	180	4,949	22,014	8.30	3.76
NEW ER115.0750	11.50	292	5.00	127	750	131	4.62	117	6.88	175	5,160	22,953	9.05	4.11
NEW ER115.0800	11.50	292	5.00	127	800	140	4.79	122	6.71	170	5,368	23,878	9.35	4.24
NEW ER115.0850	11.50	292	5.00	127	850	149	4.74	120	6.76	172	5,746	25,559	9.65	4.38
NEW ER115.0900	11.50	292	5.00	127	900	158	5.03	128	6.47	164	5,823	25,902	10.10	4.58
NEW ER115.0950	11.50	292	5.00	127	950	166	5.11	130	6.39	162	6,071	27,005	10.45	4.74
NEW ER115.1000	11.50	292	5.00	127	1,000	175	4.92	125	6.58	167	6,580	29,269	9.85	4.47
Rear Platinum Springs 4,000 lbs. Maximum Load Spring- 5.00" O.D.														
NEW ER4K.1125.1100	11.25	286	5.00	127	1,100	193	n/a	n/a	n/a	n/a	n/a	n/a	8.68	3.94
NEW ER4K.1125.1200	11.25	286	5.00	127	1,200	210	n/a	n/a	n/a	n/a	n/a	n/a	9.76	4.43
NEW ER4K.1125.1300	11.25	286	5.00	127	1,300	228	n/a	n/a	n/a	n/a	n/a	n/a	9.28	4.21
NEW ER4K.1125.1400	11.25	286	5.00	127	1,400	245	n/a	n/a	n/a	n/a	n/a	n/a	10.69	4.85
NEW ER4K.1125.1500	11.25	286	5.00	127	1,500	263	n/a	n/a	n/a	n/a	n/a	n/a	10.93	4.96

SPRING LOCATOR | 5.00" O.D.



Part Number	Inside Diameter (Perch O.D.)		Outside Diameter (Spring I.D.)	
	inch	mm	inch	mm
Spring Locator				
NEW ESL350.4125	3.50	89	4.125	105
NEW ESL350.4188	3.50	89	4.188	106
NEW ESL375.4000	3.75	95	4.000	102
NEW ELS375.4063	3.75	95	4.063	103
NEW ESL375.4125	3.75	95	4.125	105
NEW ESL375.4188	3.75	95	4.188	106
NEW ESL375.4313	3.75	95	4.313	110
NEW ESL375.4375	3.75	95	4.375	111

COIL SLEEVE | 5.00" O.D.

Part Number	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
	inch	mm	inch	mm	inch	mm
Coil Sleeve (Fits 5.00" O.D. Springs)						
NEW CS5001 (NASCAR Approved)	4.50-6.00	114-152	0.423-0.541	11-14	13.43	341
NEW CS5001L	4.50-6.00	114-152	0.551-0.650	14-17	16.50	419
NEW CS5002 (NASCAR Approved)	4.50-6.00	114-152	0.551-0.650	14-17	13.43	341
NEW CS5002L	4.50-6.00	114-152	0.551-0.650	14-17	16.50	419

	Fitment Length	
	inch	mm
SPRING BAGS-Pair (Fits 5.00" O.D. Springs)		
NEW ESB14.300	12.00-14.00	305-356
NEW ESB16.300	14.00-16.00	356-406
NEW ESB14.300	12.00-14.00	305-356
ESB16.300	14.00-16.00	356-406

TORQUE LINK SPRING

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kg
Torque Link Spring														
NEW 0675.500.1000	6.75	171	5.00	127	500/1000	88/175	3.66	93	3.09	78	2,711	12,059	6.15	2.79
NEW 0675.500.1500	6.75	171	5.00	127	750/1500	131/263	3.30	84	3.45	88	3,196	14,216	6.61	3.00
0700.500.0600	7.00	178	5.00	127	600	105	2.64	67	4.36	111	2,618	11,645	3.92	1.78
0700.500.0800	7.00	178	5.00	127	800	140	2.76	70	4.24	108	3,390	15,079	4.43	2.01

COIL-OVER | 60mm I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
80 (length in mm)														
80-60-0100	80	3.15	60	2.36	100	571	31	1.22	49	1.93	4,901	1,102	0.38	0.84
80-60-0120	80	3.15	60	2.36	120	685	33	1.30	47	1.85	5,622	1,264	0.43	0.95
80-60-0140	80	3.15	60	2.36	140	800	35	1.38	45	1.77	6,321	1,421	0.47	1.04
80-60-0160	80	3.15	60	2.36	160	914	35	1.38	45	1.77	7,172	1,612	0.49	1.08
80-60-0180	80	3.15	60	2.36	180	1,028	37	1.46	43	1.69	7,668	1,724	0.55	1.21
80-60-0200	80	3.15	60	2.36	200	1,142	38	1.50	42	1.65	8,350	1,877	0.58	1.28
80-60-0220	80	3.15	60	2.36	220	1,256	39	1.54	41	1.61	9,125	2,051	0.60	1.32
80-60-0240	80	3.15	60	2.36	240	1,371	39	1.54	41	1.61	9,753	2,193	0.63	1.39
80-60-0260	80	3.15	60	2.36	260	1,485	40	1.57	40	1.57	10,348	2,326	0.66	1.46
80-60-0280	80	3.15	60	2.36	280	1,599	41	1.61	39	1.54	10,910	2,453	0.69	1.52
80-60-0300	80	3.15	60	2.36	300	1,713	42	1.65	38	1.50	11,438	2,571	0.72	1.59
100 (length in mm)														
New 100-60-0070	100	3.94	60	2.36	70	400	36	1.42	64	2.52	4,512	1,014	0.42	0.93
100-60-0080	100	3.94	60	2.36	80	457	36	1.42	64	2.52	5,114	1,150	0.44	0.97
100-60-0090	100	3.94	60	2.36	90	514	37	1.46	63	2.48	5,708	1,283	0.46	1.01
100-60-0100	100	3.94	60	2.36	100	571	40	1.57	60	2.36	6,000	1,349	0.53	1.17
100-60-0110	100	3.94	60	2.36	110	628	41	1.61	59	2.32	6,490	1,459	0.56	1.23
100-60-0120	100	3.94	60	2.36	120	685	42	1.65	58	2.28	6,960	1,565	0.59	1.30
100-60-0140	100	3.94	60	2.36	140	800	41	1.61	59	2.32	8,281	1,862	0.60	1.32
100-60-0160	100	3.94	60	2.36	160	914	43	1.69	57	2.24	9,070	2,039	0.66	1.46
100-60-0180	100	3.94	60	2.36	180	1,028	43	1.69	57	2.24	10,341	2,325	0.67	1.48
100-60-0200	100	3.94	60	2.36	200	1,142	46	1.81	54	2.13	10,760	2,419	0.76	1.68
100-60-0220	100	3.94	60	2.36	220	1,256	46	1.81	54	2.13	11,894	2,674	0.77	1.70
100-60-0240	100	3.94	60	2.36	240	1,371	50	1.97	50	1.97	12,066	2,713	0.88	1.94
100-60-0260	100	3.94	60	2.36	260	1,485	51	2.01	49	1.93	12,818	2,882	0.91	2.01
100-60-0280	100	3.94	60	2.36	280	1,599	51	2.01	49	1.93	13,717	3,084	0.94	2.07
100-60-0300	100	3.94	60	2.36	300	1,713	51	2.01	49	1.93	14,610	3,284	0.97	2.14
100-60-0320	100	3.94	60	2.36	320	1,828	52	2.05	48	1.89	15,280	3,435	1.00	2.20
100-60-0340	100	3.94	60	2.36	340	1,942	53	2.09	47	1.85	15,912	3,577	1.00	2.20
100-60-0360	100	3.94	60	2.36	360	2,056	56	2.20	44	1.73	15,993	3,595	1.12	2.47
100-60-0380	100	3.94	60	2.36	380	2,170	54	2.13	46	1.81	17,423	3,917	1.09	2.40
100-60-0400	100	3.94	60	2.36	400	2,284	55	2.17	45	1.77	17,960	4,038	1.13	2.49
100-60-0450	100	3.94	60	2.36	450	2,570	57	2.24	43	1.69	19,350	4,350	1.22	2.69
100-60-0500	100	3.94	60	2.36	500	2,856	59	2.32	41	1.61	20,550	4,620	1.31	2.89
100-60-0550	100	3.94	60	2.36	550	3,141	62	2.44	38	1.50	21,120	4,748	1.42	3.13
New 100-60-0600	100	3.94	60	2.36	600	3,427	61	2.40	39	1.54	23,438	5,269	1.43	3.15
100-60-0650	100	3.94	60	2.36	650	3,712	64	2.52	36	1.42	23,628	5,312	1.55	3.42
New 100-60-0700	100	3.94	60	2.36	700	3,998	64	2.52	36	1.42	25,375	5,705	1.58	3.48
100-60-0750	100	3.94	60	2.36	750	4,283	64	2.52	36	1.42	27,131	6,099	1.61	3.55
100-60-0800	100	3.94	60	2.36	800	4,569	65	2.56	35	1.38	28,200	6,340	1.66	3.66
120 (length in mm)														
New 120-60-0040	120	4.72	60	2.36	40	228	34	0.55	86	3.39	3,424	770	0.36	0.79
120-60-0050	120	4.72	60	2.36	50	286	37	1.46	83	3.27	4,173	938	0.41	0.90
New 120-60-0060	120	4.72	60	2.36	60	343	40	1.57	80	3.15	4,824	1,084	0.47	1.04
New 120-60-0070	120	4.72	60	2.36	70	400	43	1.69	77	3.03	5,408	1,216	0.54	1.19
120-60-0080	120	4.72	60	2.36	80	457	42	1.65	78	3.07	6,246	1,404	0.54	1.19
120-60-0090	120	4.72	60	2.36	90	514	43	1.69	77	3.03	6,930	1,558	0.58	1.28
120-60-0100	120	4.72	60	2.36	100	571	44	1.73	76	2.99	7,593	1,707	0.61	1.34
120-60-0110	120	4.72	60	2.36	110	628	48	1.89	72	2.83	7,879	1,771	0.70	1.54

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	Nmm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
120-60-0120	120	4.72	60	2.36	120	685	49	1.93	71	2.80	8,526	1,917	0.73	1.61
120-60-0140	120	4.72	60	2.36	140	800	51	2.01	69	2.72	9,636	2,166	0.80	1.76
120-60-0160	120	4.72	60	2.36	160	914	53	2.09	67	2.64	10,752	2,417	0.87	1.92
120-60-0180	120	4.72	60	2.36	180	1,028	53	2.09	67	2.64	12,119	2,724	0.89	1.96
120-60-0200	120	4.72	60	2.36	200	1,142	56	2.20	64	2.52	12,780	2,873	1.00	2.20
120-60-0220	120	4.72	60	2.36	220	1,256	56	2.20	64	2.52	14,102	3,170	1.01	2.23
120-60-0240	120	4.72	60	2.36	240	1,371	58	2.28	62	2.44	14,967	3,365	1.07	2.36
120-60-0260	120	4.72	60	2.36	260	1,485	58	2.28	62	2.44	16,107	3,621	1.10	2.43
120-60-0280	120	4.72	60	2.36	280	1,599	60	2.36	60	2.36	16,853	3,789	1.15	2.54
120-60-0300	120	4.72	60	2.36	300	1,713	61	2.40	59	2.32	17,618	3,961	1.24	2.73
120-60-0320	120	4.72	60	2.36	320	1,828	64	2.52	56	2.20	17,984	4,043	1.32	2.91
120-60-0340	120	4.72	60	2.36	340	1,942	65	2.56	55	2.17	18,734	4,212	1.36	3.00
120-60-0360	120	4.72	60	2.36	360	2,056	66	2.60	54	2.13	19,440	4,370	1.42	3.13
140 (length in mm)														
140-60-0050	140	5.51	60	2.36	50	286	45	1.77	95	3.74	4,750	1,068	0.54	1.19
New 140-60-0060	140	5.51	60	2.36	60	343	48	1.89	92	3.62	5,550	1,248	0.60	1.32
New 140-60-0070	140	5.51	60	2.36	70	400	47	1.85	93	3.66	6,524	1,467	0.61	1.34
140-60-0080	140	5.51	60	2.36	80	457	50	1.97	90	3.54	7,182	1,615	0.69	1.52
140-60-0090	140	5.51	60	2.36	90	514	50	1.97	90	3.54	8,064	1,813	0.72	1.59
140-60-0100	140	5.51	60	2.36	100	571	56	2.20	84	3.31	8,390	1,886	0.84	1.85
140-60-0110	140	5.51	60	2.36	110	628	56	2.20	84	3.31	9,213	2,071	0.87	1.92
140-60-0120	140	5.51	60	2.36	120	685	56	2.20	84	3.31	10,038	2,257	0.89	1.96
140-60-0130	140	5.51	60	2.36	130	742	57	2.24	83	3.27	10,792	2,426	0.92	2.03
140-60-0140	140	5.51	60	2.36	140	800	59	2.32	81	3.19	11,368	2,556	0.97	2.14
140-60-0150	140	5.51	60	2.36	150	857	60	2.36	80	3.15	11,996	2,697	1.02	2.25
140-60-0160	140	5.51	60	2.36	160	914	63	2.48	77	3.03	12,400	2,788	1.09	2.40
140-60-0170	140	5.51	60	2.36	170	971	64	2.52	76	2.99	12,963	2,914	1.13	2.49
140-60-0180	140	5.51	60	2.36	180	1,028	66	2.60	74	2.91	13,266	2,982	1.21	2.67
140-60-0190	140	5.51	60	2.36	190	1,085	64	2.52	76	2.99	14,497	3,259	1.16	2.56
140-60-0200	140	5.51	60	2.36	200	1,142	65	2.56	75	2.95	15,015	3,376	1.21	2.67
140-60-0220	140	5.51	60	2.36	220	1,256	65	2.56	75	2.95	16,544	3,719	1.23	2.71
140-60-0240	140	5.51	60	2.36	240	1,371	70	2.76	70	2.76	16,800	3,777	1.39	3.06
140-60-0260	140	5.51	60	2.36	260	1,485	71	2.80	69	2.72	17,875	4,018	1.45	3.20
140-60-0280	140	5.51	60	2.36	280	1,599	75	2.95	65	2.56	18,137	4,077	1.59	3.51
140-60-0300	140	5.51	60	2.36	300	1,713	75	2.95	65	2.56	19,500	4,384	1.62	3.57
140-60-0350	140	5.51	60	2.36	350	1,999	80	3.15	60	2.36	20,886	4,695	1.84	4.06
140-60-0400	140	5.51	60	2.36	400	2,284	81	3.19	59	2.32	23,500	5,283	1.93	4.25
140-60-0450	140	5.51	60	2.36	450	2,570	82	3.23	58	2.28	26,066	5,860	2.02	4.45
140-60-0500	140	5.51	60	2.36	500	2,856	89	3.50	51	2.01	25,375	5,705	2.32	5.11
170 (length in mm)														
170-60-0030	170	6.69	60	2.36	30	171	47	1.85	123	4.84	3,677	827	0.52	1.15
170-60-0040	170	6.69	60	2.36	40	228	53	2.09	117	4.61	4,676	1,051	0.64	1.41
170-60-0050	170	6.69	60	2.36	50	286	54	2.13	116	4.57	5,793	1,302	0.69	1.52
New 170-60-0060	170	6.69	60	2.36	60	343	57	2.24	113	4.45	6,780	1,524	0.77	1.70
New 170-60-0070	170	6.69	60	2.36	70	400	61	2.40	109	4.29	7,600	1,709	0.88	1.94
170-60-0080	170	6.69	60	2.36	80	457	66	2.60	104	4.09	8,320	1,870	1.00	2.20
170-60-0090	170	6.69	60	2.36	90	514	70	2.76	105	4.13	8,987	2,020	1.11	2.45
170-60-0100	170	6.69	60	2.36	100	571	71	2.80	99	3.90	9,950	2,237	1.14	2.51
170-60-0110	170	6.69	60	2.36	110	628	70	2.76	100	3.94	10,978	2,468	1.17	2.58
170-60-0120	170	6.69	60	2.36	120	685	71	2.80	99	3.90	11,874	2,669	1.21	2.67

COIL-OVER | 60mm I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
170-60-0130	170	6.69	60	2.36	130	742	73	2.87	97	3.82	12,594	2,831	1.28	2.82
170-60-0140	170	6.69	60	2.36	140	800	75	2.95	95	3.74	13,358	3,003	1.33	2.93
170-60-0150	170	6.69	60	2.36	150	857	76	2.99	94	3.70	14,093	3,168	1.39	3.06
170-60-0160	170	6.69	60	2.36	160	914	78	3.07	92	3.62	14,798	3,327	1.45	3.20
170-60-0170	170	6.69	60	2.36	170	971	78	3.07	92	3.62	15,704	3,530	1.48	3.26
170-60-0180	170	6.69	60	2.36	180	1,028	81	3.19	89	3.50	15,998	3,597	1.59	3.51
170-60-0190	170	6.69	60	2.36	190	1,085	83	3.27	87	3.43	16,606	3,733	1.65	3.64
170-60-0200	170	6.69	60	2.36	200	1,142	86	3.39	84	3.31	16,900	3,799	1.75	3.86
170-60-0220	170	6.69	60	2.36	220	1,256	84	3.31	86	3.39	18,898	4,248	1.75	3.86
170-60-0240	170	6.69	60	2.36	240	1,371	89	3.50	81	3.19	19,380	4,357	1.94	4.28
170-60-0260	170	6.69	60	2.36	260	1,485	95	3.74	75	2.95	19,617	4,410	2.13	4.70
170-60-0280	170	6.69	60	2.36	280	1,599	95	3.74	75	2.95	21,140	4,752	2.17	4.78
170-60-0300	170	6.69	60	2.36	300	1,713	95	3.74	75	2.95	22,440	5,045	2.23	4.92
180 (length in mm)														
180-60-0040	180	7.09	60	2.36	40	228	58	2.28	122	4.80	4,895	1,100	0.70	1.54
180-60-0050	180	7.09	60	2.36	50	286	59	2.32	121	4.76	6,063	1,363	0.80	1.76
New 180-60-0060	180	7.09	60	2.36	60	343	63	2.48	117	4.61	7,031	1,581	0.90	1.98
New 180-60-0070	180	7.09	60	2.36	70	400	66	2.60	114	4.49	7,989	1,796	1.00	2.20
180-60-0080	180	7.09	60	2.36	80	457	71	2.80	109	4.29	8,728	1,962	1.10	2.42
180-60-0090	180	7.09	60	2.36	90	514	70	2.76	110	4.33	9,905	2,227	1.10	2.42
180-60-0100	180	7.09	60	2.36	100	571	76	2.99	104	4.09	10,404	2,339	1.30	2.87
180-60-0110	180	7.09	60	2.36	110	628	76	2.99	104	4.09	11,461	2,577	1.30	2.87
180-60-0120	180	7.09	60	2.36	120	685	77	3.03	103	4.06	12,380	2,783	1.30	2.87
180-60-0130	180	7.09	60	2.36	130	742	78	3.07	102	4.02	13,277	2,985	1.40	3.09
180-60-0140	180	7.09	60	2.36	140	800	85	3.35	95	3.74	13,315	2,993	1.60	3.53
180-60-0150	180	7.09	60	2.36	150	857	86	3.39	94	3.70	14,114	3,173	1.60	3.53
New 180-60-0170	180	7.09	60	2.36	170	971	83	3.27	97	3.82	16,502	3,710	1.60	3.53
180-60-0200	180	7.09	60	2.36	200	1,142	89	3.50	91	3.58	18,223	4,097	1.80	3.97
200 (length in mm)														
200-60-0030	200	7.87	60	2.36	30	171	61	2.40	140	5.51	4,163	936	0.72	1.59
200-60-0040	200	7.87	60	2.36	40	228	65	2.56	135	5.31	5,416	1,218	0.83	1.83
200-60-0050	200	7.87	60	2.36	50	286	66	2.60	134	5.28	6,700	1,506	0.89	1.96
New 200-60-0060	200	7.87	60	2.36	60	343	75	2.95	131	5.16	7,485	1,683	1.11	2.45
New 200-60-0070	200	7.87	60	2.36	70	400	73	2.87	127	5.00	8,918	2,005	1.10	2.42
200-60-0080	200	7.87	60	2.36	80	457	78	3.07	122	4.80	9,790	2,201	1.24	2.73
200-60-0090	200	7.87	60	2.36	90	514	83	3.27	117	4.61	10,548	2,371	1.39	3.06
200-60-0100	200	7.87	60	2.36	100	571	83	3.27	117	4.61	11,731	2,637	1.42	3.13
200-60-0110	200	7.87	60	2.36	110	628	91	3.58	109	4.29	12,042	2,707	1.63	3.59
200-60-0120	200	7.87	60	2.36	120	685	91	3.58	109	4.29	13,080	2,941	1.67	3.68
250 (length in mm)														
250-60-0025	250	9.84	60	2.36	25	143	69	2.72	181	7.13	4,522	1,017	0.81	1.79
250-60-0030	250	9.84	60	2.36	30	171	74	2.91	176	6.93	5,280	1,187	0.92	2.03
250-60-0035	250	9.84	60	2.36	35	200	80	3.15	170	6.69	5,935	1,334	1.06	2.34
250-60-0040	250	9.84	60	2.36	40	228	80	3.15	170	6.69	6,820	1,533	1.08	2.38
250-60-0045	250	9.84	60	2.36	45	257	88	3.46	162	6.38	7,305	1,642	1.26	2.78
250-60-0050	250	9.84	60	2.36	50	286	88	3.46	162	6.38	8,093	1,819	1.30	2.87
New 250-60-0060	250	9.84	60	2.36	60	343	91	3.58	159	6.26	9,533	2,143	1.42	3.13
New 250-60-0070	250	9.84	60	2.36	70	400	95	3.74	155	6.10	10,838	2,436	1.56	3.44
250-60-0080	250	9.84	60	2.36	80	457	99	3.90	151	5.94	12,062	2,712	1.70	3.75
250-60-0090	250	9.84	60	2.36	90	514	106	4.17	144	5.67	12,976	2,917	1.91	4.21

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
250-60-0100	250	9.84	60	2.36	100	571	113	4.45	137	5.39	13,671	3,073	2.14	4.72
250-60-0110	250	9.84	60	2.36	110	628	113	4.45	137	5.39	15,100	3,395	2.17	4.78
250-60-0120	250	9.84	60	2.36	120	685	120	4.72	130	5.12	15,552	3,496	2.43	5.36
300 (length in mm)														
300-60-0020	300	11.81	60	2.36	20	114	84	3.31	216	8.50	4,320	971	0.99	2.18
300-60-0025	300	11.81	60	2.36	25	143	87	3.43	213	8.39	5,315	1,195	1.09	2.40
300-60-0030	300	11.81	60	2.36	30	171	93	3.66	207	8.15	6,221	1,399	1.23	2.71
300-60-0035	300	11.81	60	2.36	35	200	99	3.90	201	7.91	7,020	1,578	1.40	3.09
300-60-0040	300	11.81	60	2.36	40	228	108	4.25	192	7.56	7,700	1,731	1.60	3.53
300-60-0045	300	11.81	60	2.36	45	257	107	4.21	193	7.60	8,699	1,956	1.63	3.59
300-60-0050	300	11.81	60	2.36	50	286	117	4.61	183	7.20	9,164	2,060	1.87	4.12
New 300-60-0060	300	11.81	60	2.36	60	343	118	4.65	182	7.17	10,908	2,452	1.99	4.39
New 300-60-0070	300	11.81	60	2.36	70	400	132	5.20	168	6.61	11,763	2,644	2.39	5.27
300-60-0080	300	11.81	60	2.36	80	457	137	5.39	163	6.42	13,029	2,929	2.60	5.73
300-60-0090	300	11.81	60	2.36	90	514	134	5.28	166	6.54	14,972	3,366	2.59	5.71
300-60-0100	300	11.81	60	2.36	100	571	141	5.55	159	6.26	15,860	3,565	2.86	6.31
350 (length in mm)														
350-60-0020	350	13.78	60	2.36	20	114	106	4.17	244	9.61	4,882	1,098	1.33	2.93
350-60-0025	350	13.78	60	2.36	25	143	108	4.25	242	9.53	6,044	1,359	1.44	3.17
350-60-0030	350	13.78	60	2.36	30	171	114	4.49	236	9.29	7,087	1,593	1.60	3.53
350-60-0035	350	13.78	60	2.36	35	200	121	4.76	229	9.02	8,017	1,802	1.80	3.97
350-60-0040	350	13.78	60	2.36	40	228	130	5.12	220	8.66	8,803	1,979	2.04	4.50
350-60-0045	350	13.78	60	2.36	45	257	140	5.51	210	8.27	9,458	2,126	2.31	5.09
350-60-0050	350	13.78	60	2.36	50	286	139	5.47	211	8.31	10,540	2,369	2.35	5.18
350-60-0055	350	13.78	60	2.36	55	314	139	5.47	211	8.31	11,603	2,608	2.41	5.31
Tender/Linear														
New 30-60-0120	70	2.76	60	2.36	120	685	40	1.57	30	1.18	3,595	808	0.78	1.72
New 35-60-0065	60	2.36	60	2.36	65	371	25	0.98	35	1.38	2,431	547	0.45	0.99
New 40-60-0020	55	2.17	60	2.36	20	114	15	0.59	40	1.57	804	181	0.25	0.55
New 40-60-0030	65	2.56	60	2.36	30	171	25	0.99	40	1.57	1,260	283	0.34	0.75
New 40-60-0040	75	2.95	60	2.36	40	228	35	1.38	40	1.57	1,616	363	0.65	1.43
New 40-60-0050	68	2.68	60	2.36	50	286	28	1.11	40	1.57	2,180	490	0.56	1.23
New 40-60-0055	68	2.68	60	2.36	55	314	28	1.11	40	1.57	2,365	532	0.50	1.10
New 40-60-0060	66	2.60	60	2.36	60	343	26	1.03	40	1.57	2,514	565	0.48	1.06
New 40-60-0070	65	2.56	60	2.36	70	400	25	0.99	40	1.57	3,042	684	0.57	1.26
New 40-60-0120	80	3.15	60	2.36	120	685	40	1.57	40	1.57	4,795	1,078	0.78	1.72
New 50-60-0020	78	3.07	60	2.36	20	114	28	1.10	50	1.97	1,000	225	0.47	1.04
New 50-60-0030	90	3.54	60	2.36	30	171	40	1.57	50	1.97	1,578	355	0.82	1.81
New 50-60-0065	82	3.23	60	2.36	65	371	32	1.26	50	1.97	3,447	775	0.62	1.37
New 50-60-0120	90	3.54	60	2.36	120	685	40	1.57	50	1.97	5,995	1,348	0.78	1.72
60-60-0030	101	3.98	60	2.36	30	171	41	1.62	60	2.36	1,878	422	0.82	1.81
60-60-0040	113	4.45	60	2.36	40	228	53	2.09	60	2.36	2,510	564	0.95	2.09
60-60-0050	105	4.13	60	2.36	50	286	45	1.77	60	2.36	3,020	679	0.86	1.90
New 60-60-0060	96	3.78	60	2.36	60	343	36	1.42	60	2.36	3,798	854	0.66	1.45
New 60-60-0070	95	3.74	60	2.36	70	400	35	1.38	60	2.36	4,183	940	0.72	1.59
New 70-60-0030	108	4.25	60	2.36	30	171	38	1.50	70	2.76	2,178	490	0.82	1.81
Tender/Progressive														
New 50-60-0040/0120	106	4.17	60	2.36	40/120	228/385	56	2.20	50	1.97	3,800	854	0.70	1.54
New 50-60-0060/0150	117	4.61	60	2.36	60/150	343/857	67	2.64	50	1.97	5,000	1,124	1.20	2.65

COIL-OVER | 60mm I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
Helper														
60-60-0002	75	2.87	60	2.36	2	11	9	0.51	66	2.60	133	30	0.12	0.26
80-60-0010	104	4.09	60	2.36	10	57	24	0.94	80	3.15	800	180	0.41	0.90
100-60-0010	124	4.88	60	2.36	10	57	24	0.94	100	3.94	1,000	225	0.41	0.90
Coupling Spacer														
1-60-00 (Spring Coupler)														
Adapter														
ADAPTER60-250 (Perch Adapter 60mm to 2.50")			60/2.50	60 / 64										



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
200 (length in mm)														
200-70-0050	200	7.87	70	2.76	50	286	65	2.56	135	5.31	6,750	1,517	1.10	2.42
200-70-0055	200	7.87	70	2.76	55	314	65	2.56	135	5.31	7,425	1,669	1.10	2.42
New 200-70-0060	200	7.87	70	3.71	60	343	67	2.64	133	5.23	7,980	1,794	1.20	2.65
200-70-0065	200	7.87	70	2.76	65	371	68	2.68	132	5.20	8,580	1,929	1.20	2.64
New 200-70-0070	200	7.87	70	2.76	70	400	70	2.76	130	5.12	9,100	2,046	1.30	2.87
200-70-0075	200	7.87	70	2.76	75	428	72	2.83	128	5.04	9,600	2,158	1.40	3.09
200-70-0080	200	7.87	70	3.79	80	457	74	2.91	126	4.96	10,080	2,266	1.40	3.09
200-70-0085	200	7.87	70	2.76	85	485	76	2.99	124	4.88	10,540	2,369	1.50	3.31
200-70-0090	200	7.87	70	2.76	90	514	78	3.07	122	4.80	10,980	2,468	1.60	3.53
200-70-0100	200	7.87	70	2.76	100	571	77	3.03	123	4.84	12,300	2,765	1.60	3.53
200-70-0110	200	7.87	70	2.76	110	628	83	3.27	117	4.61	12,870	2,893	1.80	3.97
New 200-70-0120	200	7.87	70	2.76	120	685	83	3.27	117	4.61	10,040	2,257	1.80	3.97
225 (length in mm)														
225-70-0050	225	8.86	70	2.76	50	286	77	3.03	148	5.83	7,400	1,664	1.40	3.09
225-70-0055	225	8.86	70	2.76	55	314	78	3.07	147	5.79	8,085	1,818	1.40	3.09
New 225-70-0060	225	8.86	70	2.76	60	343	79	3.11	146	5.75	8,760	1,969	1.50	3.31
225-70-0065	225	8.86	70	2.76	65	371	80	3.15	145	5.71	9,425	2,119	1.50	3.31
New 225-70-0070	225	8.86	70	2.76	70	400	82	3.23	143	5.63	10,010	2,250	1.60	3.53
225-70-0075	225	8.86	70	2.76	75	428	84	3.31	141	5.55	10,575	2,377	1.70	3.75
225-70-0080	225	8.86	70	2.76	80	457	86	3.39	139	5.47	11,120	2,500	1.70	3.75
225-70-0085	225	8.86	70	2.76	85	485	88	3.46	137	5.39	11,645	2,618	1.80	3.97
225-70-0090	225	8.86	70	2.76	90	514	85	3.35	140	5.51	12,600	2,833	1.70	3.75
225-70-0100	225	8.86	70	2.76	100	571	90	3.54	135	5.31	13,500	3,035	1.90	4.19
225-70-0110	225	8.86	70	2.76	110	628	95	3.74	130	5.12	14,300	3,215	2.10	4.63
225-70-0120	225	8.86	70	2.76	120	685	95	3.74	130	5.12	15,600	3,507	2.20	4.85
250 (length in mm)														
250-70-0040	250	9.84	70	2.76	40	228	77	3.03	173	6.81	6,920	1,556	1.30	2.87
250-70-0045	250	9.84	70	2.76	45	257	77	3.03	173	6.81	7,785	1,750	1.30	2.87
250-70-0050	250	9.84	70	2.76	50	286	84	3.31	166	6.54	8,300	1,866	1.50	3.31
250-70-0055	250	9.84	70	2.76	55	314	85	3.35	165	6.50	9,075	2,040	1.60	3.53
New 250-70-0060	250	9.84	70	2.76	60	343	86	3.39	164	6.46	9,840	2,212	1.60	3.53
250-70-0065	250	9.84	70	2.76	65	371	87	3.43	163	6.42	10,595	2,382	1.70	3.75
New 250-70-0070	250	9.84	70	2.76	70	400	89	3.50	161	6.34	11,270	2,534	1.80	3.97
250-70-0075	250	9.84	70	2.76	75	428	91	3.58	159	6.26	11,925	2,681	1.80	3.97
250-70-0080	250	9.84	70	2.76	80	457	93	3.66	157	6.18	12,560	2,824	1.90	4.19
250-70-0085	250	9.84	70	2.76	85	485	95	3.74	155	6.10	13,175	2,962	2.00	4.41
250-70-0090	250	9.84	70	2.76	90	514	97	3.82	153	6.02	13,770	3,096	2.10	4.63
250-70-0100	250	9.84	70	2.76	100	571	103	4.06	147	5.79	14,700	3,305	2.30	5.07
250-70-0110	250	9.84	70	2.76	110	628	102	4.02	148	5.83	16,280	3,660	2.40	5.29
250-70-0120	250	9.84	70	2.76	120	685	108	4.25	142	5.59	17,040	3,831	2.60	5.73
300 (length in mm)														
300-70-0020	300	11.81	70	2.76	20	114	75	2.95	225	8.86	4,500	1,012	1.10	2.42
300-70-0025	300	11.81	70	2.76	25	143	78	3.07	222	8.74	5,550	1,248	1.20	2.64
300-70-0030	300	11.81	70	2.76	30	171	90	3.54	210	8.27	6,300	1,416	1.50	3.31
300-70-0035	300	11.81	70	2.76	35	200	95	3.74	205	8.07	7,175	1,613	1.60	3.53
300-70-0040	300	11.81	70	2.76	40	228	93	3.66	207	8.15	8,280	1,861	1.60	3.53
300-70-0045	300	11.81	70	2.76	45	257	100	3.94	200	7.87	9,000	2,023	1.90	4.19
300-70-0050	300	11.81	70	2.76	50	286	100	3.94	200	7.87	10,000	2,248	1.90	4.19
300-70-0055	300	11.81	70	2.76	55	314	109	4.29	191	7.52	10,505	2,362	2.20	4.85
New 300-70-0060	300	11.81	70	2.76	60	343	109	4.29	191	7.52	11,460	2,576	2.20	4.85

COIL-OVER | 70mm I.D.

Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
350 (length in mm)														
350-70-0020	350	13.78	70	2.76	20	114	94	3.70	256	10.08	5,120	1,151	1.40	3.09
350-70-0025	350	13.78	70	2.76	25	143	95	3.74	255	10.04	6,375	1,433	1.50	3.31
350-70-0030	350	13.78	70	2.76	30	171	108	4.25	242	9.53	7,260	1,632	1.90	4.19
350-70-0035	350	13.78	70	2.76	35	200	114	4.49	236	9.29	8,260	1,857	2.10	4.63
350-70-0040	350	13.78	70	2.76	40	228	111	4.37	239	9.41	9,560	2,149	2.10	4.63
350-70-0045	350	13.78	70	2.76	45	257	119	4.69	231	9.09	10,395	2,337	2.30	5.07
350-70-0050	350	13.78	70	2.76	50	286	128	5.04	222	8.74	11,100	2,495	2.60	5.73
350-70-0055	350	13.78	70	2.76	55	314	127	5.00	223	8.78	12,265	2,757	2.70	5.95
New 350-70-0060	350	13.78	70	2.76	60	343	127	5.00	223	8.78	13,380	3,008	2.70	5.95
Tender/Linear														
New 40-70-0030	82	3.23	70	2.76	30	171								
New 40-70-0040	78	3.07	70	2.76	40	228								
New 40-70-0050	69	2.72	70	2.76	50	286								
New 40-70-0060	71	2.80	70	2.76	60	343								
60-70-0045	98	3.86	70	2.76	45	257								
70-70-0015	97	3.82	70	2.76	15	86								
70-70-0030	118	4.65	70	2.76	30	171								
70-70-0034	108	4.25	70	2.76	34	194								
70-70-0038	111	4.37	70	2.76	38	217								
70-70-0042	111	4.37	70	2.76	42	240								
70-70-0046	106	4.17	70	2.76	46	263								
70-70-0050	121	4.76	70	2.76	50	286								
New 70-70-0060	121	4.76	70	2.76	60	343								
Helper														
New 80-70-0003	93	3.66	70	2.76	3	17								
Coupling Spacer														
01-70-00 (Spring Coupler)														



Part Number	Length		Inside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	mm	inch	mm	inch	N/mm	lbs/inch	mm	inch	mm	inch	N	lbs	kg	lbs
F3 Standard														
F3 C400	141	5.55	36	1.42	70	400	74	2.91	67	2.64	4,672	1,050	0.50	1.10
F3 C450	139	5.47	36	1.42	79	451	78	3.07	61	2.40	4,806	1,080	0.54	1.19
F3 C500	136	5.35	36	1.42	88	503	77	3.03	59	2.32	5,117	1,150	0.54	1.19
F3 C550	134	5.28	36	1.42	96	548	79	3.11	55	2.17	5,295	1,190	0.59	1.30
F3 C600	133	5.24	36	1.42	105	600	75	2.95	58	2.28	6,096	1,370	0.59	1.30
F3 C700	130	5.12	36	1.42	123	702	79	3.11	51	2.01	6,274	1,410	0.64	1.41
F3 C800	128	5.04	36	1.42	140	800	78	3.07	50	1.97	6,986	1,571	0.64	1.41
F3 C900	127	5.00	36	1.42	158	902	76	2.99	51	2.01	8,099	1,821	0.68	1.50
F3 C1000	126	4.96	36	1.42	175	999	79	3.11	47	1.85	8,188	1,841	0.73	1.61
F3 C1100	125	4.92	36	1.42	193	1,102	80	3.15	45	1.77	8,588	1,931	0.73	1.61
F3 C1200	124	4.88	36	1.42	210	1,199	83	3.27	41	1.61	8,499	1,911	0.77	1.70
F3 C1300	123	4.84	36	1.42	228	1,302	83	3.27	40	1.57	8,989	2,021	0.82	1.81
F3 C1400	123	4.84	36	1.42	245	1,399	81	3.19	42	1.65	10,012	2,251	0.77	1.70
F3 C1500	122	4.80	36	1.42	263	1,502	80	3.15	42	1.65	11,036	2,481	0.77	1.70
F3 C1600	122	4.80	36	1.42	280	1,599	84	3.31	38	1.50	10,591	2,381	0.86	1.90
F3 C1800	121	4.76	36	1.42	315	1,799	82	3.23	39	1.54	12,281	2,761	0.86	1.90
F3 C2000	121	4.76	36	1.42	350	1,999	83	3.27	38	1.50	13,305	2,991	0.86	1.90
F3 Short														
40494	111	4.37	36	1.42	105	600	59	2.32	52	2.05	5,500	1,236	0.42	0.93
40495	103	4.06	36	1.42	114	651	55	2.17	48	1.89	5,500	1,236	0.39	0.86
40496	97	3.82	36	1.42	123	702	52	2.05	45	1.77	5,500	1,236	0.37	0.82
40497	91	3.58	36	1.42	131	748	49	1.93	42	1.65	5,500	1,236	0.35	0.77
40498	86	3.39	36	1.42	140	800	47	1.85	39	1.54	5,500	1,236	0.33	0.73
40499	82	3.23	36	1.42	149	851	45	1.77	37	1.46	5,500	1,236	0.32	0.71
40500	78	3.07	36	1.42	158	902	43	1.69	35	1.38	5,500	1,236	0.30	0.66
40501	74	2.91	36	1.42	166	948	41	1.61	33	1.30	5,500	1,236	0.29	0.64
40502	71	2.80	36	1.42	175	999	40	1.57	31	1.22	5,500	1,236	0.28	0.62
40503	68	2.68	36	1.42	184	1,051	38	1.50	30	1.18	5,500	1,236	0.27	0.60
40504	66	2.60	36	1.42	193	1,102	37	1.46	29	1.14	5,500	1,236	0.26	0.57
54587	63	2.48	36	1.42	201	1,148	36	1.42	27	1.06	5,500	1,236	0.25	0.55
54588	61	2.40	36	1.42	210	1,199	35	1.38	26	1.02	5,500	1,236	0.25	0.55
54589	59	2.32	36	1.42	219	1,251	34	1.34	25	0.98	5,500	1,236	0.24	0.53
54590	58	2.28	36	1.42	228	1,302	34	1.34	24	0.94	5,500	1,236	0.23	0.51

