Installation Instructions

Eibach Springs, Inc. • 264 Mariah Circle • Corona, California 92879-1751 • USA • Tech Support 800-222-8811 Ext 114



PRO-KIT-#7714.140

SUBARU- WRX - 2004

Kit Contents	Description	Part Number	Qty	
	Front Spring	7714.001	2	
	Rear Spring	7714.002	2	
	Information Kit	EPAK	1	
	Instructions	7714.140INST	1	

NOTES: Read All Instructions Before Beginning Installation

- Installation of a *PRO-KIT* Spring set should only be performed by a qualified mechanic experienced in the installation and removal of suspension springs.
- **Use** of a hoist is highly recommended and will substantially reduce installation time.
- Never work on or under a vehicle unless it is properly supported by safety stands and wheels are blocked.
- PRO-KIT Springs are marked with the number 01 and 02 (located at the end of the part number) designating front
 and rear springs respectively.
- **PRO-KIT** Springs should be installed with the **Eibach** Logo right side up. All original stock spring isolators, dampers and tubing should be retained from the stock springs and used when installing the **PRO-KIT** Springs.
- After installation, it is always important to inspect and adjust the following if necessary:
 - Wheel alignment such as camber, caster & toe
 - Tire and/or wheel fender clearance
 - Brake line clearance and attachments
 - Brake anti-locking and anti-skid system sensors
- Tire Rotation: In order to increase the life of your tires, it is recommended to rotate your tires every 3,000 miles.

ALIGNMENT:

After installation, it will be necessary to perform a full vehicle alignment using factory specifications. *EIBACH* offers the following alignment kits for this vehicle:

Part #	Front of	<u>or Rear </u>	Camber Adjustment	
5.8126	0K Front	+/-	1.75°	
5.8126	0K Rear	+/-	1.75°	

